



Designation: C 308 – 9500

Standard Test Methods for Working, Initial Setting, and Service Strength Setting Times of Chemical-Resistant Resin Mortars¹

This standard is issued under the fixed designation C 308; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 These test methods cover the determination of the working, initial setting, and service strength setting times of chemical-resistant resin mortars.

1.2 The values stated in SI units are to be regarded as the standard. The values given in parentheses are for information only.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 *ASTM Standards:*

¹ These test methods are under the jurisdiction of Committee C-3 on Chemical-Resistant Nonmetallic Materials and are the direct responsibility of Subcommittee C03.01 on Test Methods.

Current edition approved Nov. ~~March~~ 10, 1995; 2000. Published January 1996; March 2000. Originally published as C 308–53T. Last previous edition C 308–85 (1990); C 308–95.