



**METRIC**  
Designation: A 563M – 013

## Standard Specification for Carbon and Alloy Steel Nuts [Metric]<sup>1</sup>

This standard is issued under the fixed designation A 563M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

*This standard has been approved for use by agencies of the Department of Defense.*

### 1. Scope\*

1.1 This specification covers chemical and mechanical requirements for eight property classes of hex and hex-flange carbon and alloy steel nuts for general structural and mechanical uses on bolts, studs, and other externally threaded parts.

NOTE 1—Throughout this specification, the term class means property class.

NOTE 2—Requirements for the four classes 5, 9, 10, and 12 are essentially identical with requirements given for these classes in ISO 898/II. Requirements for Classes 8S and 10S are essentially identical with requirements in an ISO 4775 Hexagon Nuts for High-Strength Structural Bolting with Large Width Across Flats, Product Grade B, Property Classes 8 and 10. Classes 8S3 and 10S3 are not recognized in ISO standards.

1.2 Classes 8S3 and 10S3 nuts have atmospheric corrosion resistance and weathering characteristics comparable to those of the steels covered in Specification A 588/A 588M. The atmospheric corrosion resistance of these steels is substantially better than that of carbon steel with or without copper addition (see 5.2). When properly exposed to the atmosphere, these steels can be used bare (uncoated) for many applications.

1.3 The nut size range for which each class is applicable is given in the table on mechanical requirements.

1.4 Appendix X1 gives guidance to assist designers and purchasers in the selection of a suitable class.

1.5 Appendix X2 gives data on the properties of slotted hex nuts and hex jam nuts.

NOTE 3—This specification is the metric companion of Specification A 563.

1.6 Terms used in this specification are defined in Specification F 1789 unless otherwise defined herein.

### 2. Referenced Documents

2.1 *ASTM Standards:*

<sup>1</sup> This specification is under the jurisdiction of ASTM Committee F16 on Fasteners and is the direct responsibility of Subcommittee F16.02 on Steel Bolts, Nuts, Rivets, and Washers.

Current edition approved Oct. 10, 2001<sup>3</sup>. Published December 2001. ~~Originally published as A 563M – 80, approved in 1980. Last previous edition approved in 2001 as A 563M – 001.~~ October 2003.

**\*A Summary of Changes section appears at the end of this standard.**