



Standard Specification for Brass Wire¹

This standard is issued under the fixed designation B 134/B 134M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the Department of Defense.

1. Scope *

1.1 This specification establishes requirements for round, hexagonal, octagonal, rectangular and square brass wire of UNS Alloys C21000, C22000, C22600, C23000, C23400, C24000, C26000, C27000, and C27400.

1.2 *Units*—The values stated in either inch-pound or SI units are to be regarded separately as standard. Within the text and tables, the SI units are shown in brackets. The values stated in each system may not be exact equivalents; therefore, each system shall be used independently of the other. Combining values from the two systems may result in nonconformance with the standard.

2. Referenced Documents

2.1 ASTM Standards:

B 250 Specification for General Requirements for Wrought Copper-Alloy Wire²

B 250M Specification for General Requirements for Wrought Copper-Alloy Wire (Metric)²

B 601 Practice for Temper Designations for Copper and Copper Alloys—Wrought and Cast²

E 8 Test Methods for Tension Testing of Metallic Materials³

E 8M Test Methods for Tension Testing of Metallic Materials (Metric)³

E 112 Test Methods for Determining the Average Grain Size³

E 478 Test Methods for Chemical Analysis of Copper Alloys⁴

3. General Requirements

3.1 The following sections of Specification B 250 or B 250M constitute a part of this specification.

3.1.1 Terminology,

3.1.2 Materials and Manufacture,

3.1.3 Workmanship, Finish and Appearance,

3.1.4 Sampling,

3.1.5 Number of Tests and Retests,

3.1.6 Specimen Preparation,

3.1.7 Test Methods,

3.1.8 Significance of Numerical limits,

3.1.9 Inspection,

3.1.10 Rejection and Rehearing,

3.1.11 Certification,

3.1.12 Mill Test Reports,

3.1.13 Product Marking,

3.1.14 Packaging and Package Marking,

3.1.15 Supplementary Requirements.

3.2 In addition, when a section with a title identical to that referenced in 3.1 appears in this specification, it contains additional requirements that supplement those that appear in Specification B 250 or B 250M.

4. Ordering Information

4.1 Include the following information in orders for product:

4.1.1 ASTM Designation and year of issue,

4.1.2 Copper Alloy UNS No. designation,

4.1.3 Temper,

4.1.4 Cross section (round, hexagonal, octagonal, rectangular, or square),

4.1.5 Quantity; total weight, footage, or number of pieces of each temper, cross section, or alloy,

4.1.6 Dimensions; diameter or distance between parallel surfaces, width and thickness, length,

4.1.7 Type of edge; square corners, rounded edge, full-rounded edge,

4.1.8 How furnished; coil, spool, or reel, specific lengths with or without ends, and

4.1.9 When material is purchased for agencies of the U.S. Government (Specification B 250 or B 250M).

4.2 The following options are available to this specification and should be specified in the contract or purchase order when required:

4.2.1 Certification (Specification B 250 or B 250M), and

4.2.2 Mill Test Report (Specification B 250 or B 250M).

¹ This specification is under the jurisdiction of ASTM Committee B05 on Copper and Copper Alloys and is the direct responsibility of Subcommittee B05.02 on Rod, Bar, Wire, Shapes, and Forgings.

Current edition approved June 10, 2001. Published September 2001. Originally published as B 134 – 40 T. Last previous edition B 134 – 96.

² *Annual Book of ASTM Standards*, Vol 02.01.

³ *Annual Book of ASTM Standards*, Vol 03.01.

⁴ *Annual Book of ASTM Standards*, Vol 03.06.