This document is not an ASTM standard and is intended only to provide the user of an ASTM standard an indication of what changes have been made to the previous version. Because it may not be technically possible to adequately depict all changes accurately, ASTM recommends that users consult prior editions as appropriate. In all cases only the current version of the standard as published by ASTM is to be considered the official document.

Designation: C 315 – 0~~0~~2

Standard Specification for Clay Flue ~~Linings~~ Liners[1]

This standard is issued under the fixed designation C 315; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the Department of Defense.

1. Scope

1.1 This specification establishes the criteria for acceptance, prior to installation, of clay flue ~~linings~~ liners used for conveying hot gases in masonry chimneys.

1.2 The values stated in inch-pound units are to be regarded as the standard. The values given in parentheses are for information only.

1.3 For installation of clay flue liners, see Practice C 1283.

2. Referenced Documents

2.1 *ASTM Standards:*

[1] This specification is under the jurisdiction of ASTM Committee ~~C-4~~ C04 on Vitrified Clay Pipe and is the direct responsibility of Subcommittee C04.20 on Methods of Test and Specifications.

Current edition approved Jan. 10, 200~~0~~2. Published March 200~~0~~2. Originally published as C 315–53. Last previous edition ~~C 315–98b.~~ C 315–00.

Copyright © ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States.