



Designation: C 348 – 9702

Standard Test Method for Flexural Strength of Hydraulic-Cement Mortars¹

This standard is issued under the fixed designation C 348; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

- 1.1 This test method covers the determination of the flexural strength of hydraulic-cement mortars.
- 1.2 The values stated in SI units are to be regarded as the standard. The values shown in parentheses are for information only.
- 1.3 Values in SI units shall be obtained by measurement in SI units or by appropriate conversion, using the Rules for Conversion and rounding given in Standard IEEE/ASTM SI 10, of measurements made in other units.
- 1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory*

¹ This test method is under the jurisdiction of ASTM Committee C-1 C01 on Cement and is the direct responsibility of Subcommittee C01.27 on Strength. Current edition approved May 10, 1997. 2002. Published June 1998. August 2002. Originally published as C 348 – 54 T. Last previous edition C 348 – 957.