



Designation: C 681 – 9903

Standard Test Method for Volatility of Oil- and Resin-Based, Knife-Grade, Channel Glazing Compounds¹

This standard is issued under the fixed designation C 681; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method describes the determination of the volatility of oil- and resin-based, knife-grade, channel glazing compounds.

1.2 The values stated in inch-pound units are to be regarded as the standard. The values given in parentheses are for information only.

1.3 The subcommittee with jurisdiction is not aware of any similar ISO standard.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 *ASTM Standards:*

¹ This test method is under the jurisdiction of ASTM Committee C24 on Building Seals and Sealants and is the direct responsibility of Subcommittee C24.20 on General Sealant Standards.

Current edition approved Feb. 10, 1999; 2003. Published May 1999; June 2003. Originally published as C 68 – 71 T; approved in 1971. Last previous edition approved in 1999 as C 681 – 949.