



Designation: C 788 – 9803

Standard Specification for Nuclear-Grade Uranyl Nitrate Solution or Crystals¹

This standard is issued under the fixed designation C 788; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification applies to nuclear-grade aqueous uranyl nitrate solution or crystals not exceeding 5 % ²³⁵U intended for subsequent manufacture into either UF₆ (for feed to an enrichment plant) or direct conversion to uranium oxide (for use in reactors).

1.2 This specification is intended to provide the nuclear industry with a general standard for aqueous uranyl nitrate solution or crystals. It recognizes the diversity of manufacturing methods and the processes to which it is subsequently to be subjected. It is therefore anticipated that it may be necessary to include supplementary specification limits by agreement between purchaser and manufacturer. Different limits are appropriate depending on whether or not the uranyl nitrate is to be converted to UF₆ for subsequent processing.

1.3 The purpose of this specification is: (a) to define the impurity and uranium isotope limits for commercial standard uranyl nitrate, and (b) to define additional limits for reprocessed uranyl nitrate (or any mixture of reprocessed and commercial standard uranyl nitrate). For such uranyl nitrates, special provisions may need to be made to ensure that no extra hazard arises to the employees, the process equipment, or the environment.

1.4 The scope of this specification does not comprehensively cover all provisions for preventing criticality accidents, for health and safety, or for shipping. Observance of this standard does not relieve the user of the obligation to conform to all international, federal, state and local regulations for processing, shipping, or any other way of using the uranyl nitrate. An example of a U.S.

¹ This specification is under the jurisdiction of ASTM Committee C-26 on Nuclear Fuel Cycle and is the direct responsibility of Subcommittee C26.02 on Fuel and Fertile Material Specifications.

Current edition approved July 10, ~~1998~~, 2003. Published ~~November 1998~~, August 2003. Originally published as C 788 – 76. Last previous edition C 788 – 938.