



Standard Practice for In-Situ Measurements of Heat Flux in Industrial Thermal Insulation Using Heat Flux Transducers¹

This standard is issued under the fixed designation C1041; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This practice covers the in-situ measurement of heat flux through industrial thermal insulation using a heat flux transducer (HFT).

1.2 The values stated in SI units are to be regarded as the standard. The values given in parentheses are for information only.

1.3 This practice estimates the thermal transport properties of thermal insulation materials in-situ in field applications under pseudo steady-state conditions. It is not intended that this practice should be used as a substitute for more precise laboratory procedures such as Test Methods C177, C335, or C518.

1.4 This practice is limited by the relatively small area that can be covered by an HFT and by the transient effects of environmental conditions.

1.5 Temperature limitations shall be as specified by the manufacturer of the HFT.

1.6 While accurate values of heat flux are highly dependent upon proper calibrations under the conditions of use, it is acceptable to use the calibrations provided by the manufacturer of the HFT for comparative work between similar materials, aging, or other conditions of use.

NOTE 1—Further information may be found in the literature (1-6).²

1.7 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

¹ This practice is under the jurisdiction of ASTM Committee C16 on Thermal Insulation and is the direct responsibility of Subcommittee C16.30 on Thermal Measurement.

Current edition approved June 1, 2010. Published September 2010. Originally approved in 1985. Last previous edition approved in 2007 as C1041 – 85 (2007). DOI: 10.1520/C1041-10.

² The boldface numbers in parentheses refer to the list of references at the end of this standard.

2. Referenced Documents

2.1 ASTM Standards:³

C177 Test Method for Steady-State Heat Flux Measurements and Thermal Transmission Properties by Means of the Guarded-Hot-Plate Apparatus

C335 Test Method for Steady-State Heat Transfer Properties of Pipe Insulation

C518 Test Method for Steady-State Thermal Transmission Properties by Means of the Heat Flow Meter Apparatus

E220 Test Method for Calibration of Thermocouples By Comparison Techniques

E230 Specification and Temperature-Electromotive Force (EMF) Tables for Standardized Thermocouples

3. Terminology

3.1 Definitions:

3.1.1 *heat flux transducer (HFT)*—a rigid or flexible transducer in a durable housing comprised of a thermopile or equivalent for sensing the temperature drop across a thin thermal resistance layer which gives a voltage output proportional to the heat flux through the transducer.

3.1.1.1 *belt HFT*—a heat flux transducer having a belt-like configuration such that the unit can be wrapped helically around a section of pipe insulation (see Fig. 1).

3.1.1.2 *spot HFT*—a small heat flux transducer having a round, square, rectangular or other configuration for the sensitive area (see Fig. 1).

3.1.2 *pseudo steady state of HFT*—the criterion for pseudo steady-state condition is that the average HFT reading over two consecutive 5-min periods does not differ by more than 2 %. Since the time constant of an HFT is typically less than or of the order of 1 min, using a time interval of 5 min ensures that the transient effects in the HFT are averaged.

3.2 Symbols:

3.2.1 Q —heat flow, W (Btu/h).

3.2.2 q —heat flux, W/m² (Btu/h·ft²).

³ For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.