



Designation: D 97 – 024

An American National Standard

Designation: 15/95

Standard Test Method for Pour Point of Petroleum Products¹

This standard is issued under the fixed designation D 97; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval. ~~This test method~~

~~This standard has been adopted approved for use by government agencies to replace Method 201 of Federal Test Methods Standard No. 791b, and Method 4452 the Department of Federal Test Method Standard No. 141A.~~

~~This test method was adopted as a joint ASTM-IP Standard in 1965.~~ Defense.

¹ This test method is under the jurisdiction of ASTM Committee D02 on Petroleum Products and Lubricants and is the direct responsibility of Subcommittee D02.07 on Flow Properties.

Current edition approved ~~March 10, 2002; April 1, 2004.~~ Published ~~May 2002; April 2004.~~ Originally published as D 97 – 27. In approved in 1927, revised and replaced former replacing D 47. Last previous edition ~~D 97 – 96a; approved in 2002 as D 97 – 02.~~

In the IP, this test method is under the jurisdiction of the Standardization Committee. This test method was adopted as a joint ASTM-IP Standard in 1965.