



Designation: D 509 – 9803

Standard Test Methods of Sampling and Grading Rosin¹

This standard is issued under the fixed designation D 509; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 These test methods cover procedures for sampling and determining the grade of rosin delivered in commercial bags, barrels, drums or in molten form.

NOTE 1—All rosin sold in interstate commerce must be described by reference to the U. S. Standards for rosin, and is therefore subject to grading prior to such sale. The grading procedure described in these test methods is used for checking grades or regrading after the rosin has moved from the primary markets to distributing or consuming points.

1.2 The values stated in ~~inch-pound~~ SI units are to be regarded as the standard. The values given in parentheses are for information only.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 *ASTM Standards:*

¹ These test methods are under the jurisdiction of ASTM Committee ~~D-1~~ D01 on Paint and Related Coatings, Materials, and Applications and are the direct responsibility of Subcommittee D01.34 on Naval Stores.

Current edition approved ~~June~~ May 10, 1998, 2003. Published ~~August 1998~~, June 2003. Originally issued as ~~D 509 — 38~~, approved in 1938. Last previous edition ~~D 509 — 70 (1993)~~; approved in 1998 as D 509 — 98.