



Designation: D 693 – 03a

Standard Specification for Crushed Aggregate for Macadam Pavements¹

This standard is issued under the fixed designation D 693; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the Department of Defense.

1. Scope

1.1 This specification covers crushed aggregate suitable for use in the construction of dry- or water-bound macadam base courses and bituminous penetration macadam base and surface courses of pavements.

1.2 The values stated in SI units are to be regarded as standard. The inch-pound units, shown in parentheses, are for information only.

1.3 The text of this standard references notes and footnotes which provide explanatory material. These notes and footnotes (excluding those in tables and figures) shall not be considered as requirements of the standard.

¹ This method is under the jurisdiction of ASTM Committee D04 on Road and Paving Materials and is the direct responsibility of Subcommittee D04.50 on Aggregate Specifications.

Current edition approved ~~Feb. 10,~~ Dec. 1, 2003. Published ~~M~~ January 2003⁴. Originally approved in 1942. Last previous edition approved in ~~1998~~ 2003 as ~~D 693-98~~.
D 693 – 03.