



Designation: D1586/D1586M – 18^{ε1}

Standard Test Method for Standard Penetration Test (SPT) and Split-Barrel Sampling of Soils¹

This standard is issued under the fixed designation D1586/D1586M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the U.S. Department of Defense.

^{ε1} NOTE—Reference (14) was editorially corrected in April 2022.

1. Scope*

1.1 This test method describes the procedure, generally known as the Standard Penetration Test (SPT), for driving a split-barrel sampler with a 140 lb [63.5 kg] hammer dropped 30 in. [750 mm] to obtain a soil sample for identification purposes, and measure the resistance of the soil to penetration of the standard 2 in. [50 mm] diameter sampler. The SPT “*N*” value is the number of hammer blows required to drive the sampler over the depth interval of 0.5 to 1.5 ft [0.15 to 0.45 m] of a 1.5 ft [0.45 m] drive interval.

1.2 Test Method **D4633** is generally necessary to measure the drill rod energy of a given drop hammer system and using the measured drill rod energy, *N* values can be corrected to a standard energy level. Practice **D6066** uses Test Methods **D1586** and **D4633** and has additional requirements for hammers, hammer energy, and drilling methods to determine energy corrected penetration resistance of loose sands for liquefaction evaluation.

1.3 Practice **D3550/D3550M** is a similar procedure using a larger diameter split barrel sampler driven with a hammer system that may allow for a different hammer mass. The penetration resistance values from Practice **D3550/D3550M** do not comply with this standard.

1.4 Test results and identification information are used in subsurface exploration for a wide range of applications such as geotechnical, geologic, geoenvironmental, or geohydrological explorations. When detailed lithology is required for geohydrological investigations, use of continuous sampling methods (**D6282/D6282M**, **D6151/D6151M**, **D6914/D6914M**) are recommended when the incremental SPT *N* value is not needed for design purposes (see **4.1.1**).

1.5 Penetration resistance testing is typically performed at 5 ft [1.5 m] depth intervals or when a significant change of materials is observed during drilling, unless otherwise specified.

1.6 This test method is limited to use in nonlithified soils and soils whose maximum particle size is approximately less than one-half of the sampler diameter.

1.7 This test method involves use of rotary drilling equipment (Guide **D5783**, Practice **D6151/D6151M**). Other drilling and sampling procedures (Guides **D6286** and **D6169/D6169M**) are available and may be more appropriate. Considerations for hand driving or shallow sampling without boreholes are not addressed. Subsurface investigations should be recorded in accordance with Practice **D5434**. Samples should be preserved and transported in accordance with Practice **D4220/D4220M** using Group B. Soil samples should be identified by group name and symbol in accordance with Practice **D2488**.

1.8 All observed and calculated values shall conform to the guidelines for significant digits and rounding established in Practice **D6026**, unless superseded by this test method.

1.8.1 The procedures used to specify how data are collected/recorded and calculated in the standard are regarded as the industry standard. In addition, they are representative of the significant digits that generally should be retained. The procedures used do not consider material variation, purpose for obtaining the data, special purpose studies, or any considerations for the user’s objectives; and it is common practice to increase or reduce significant digits of reported data to be commensurate with these considerations. It is beyond the scope of these test methods to consider significant digits used in analysis methods for engineering data.

1.9 *Units*—The values stated in either inch-pound or SI units [presented in brackets] are to be regarded separately as standard. The values stated in each system may not be exact equivalents; therefore, each system shall be used independently of the other. Combining values from the two systems may result in non-conformance with the standard. Reporting of test results in units other than inch-pound shall not be regarded as

¹ This test method is under the jurisdiction of ASTM Committee **D18** on Soil and Rock and is the direct responsibility of Subcommittee **D18.02** on Sampling and Related Field Testing for Soil Evaluations.

Current edition approved Dec. 1, 2018. Published December 2018. Originally approved in 1958. Last previous edition approved in 2011 as D1586 – 11. DOI: 10.1520/D1586_D1586M-18E01.

*A Summary of Changes section appears at the end of this standard