



Designation: D 1718 – 9803

Standard Specification for Isobutyl Acetate (95 % Grade)¹

This standard is issued under the fixed designation D 1718; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the Department of Defense.

1. Scope*

1.1 This specification covers isobutyl acetate (95 % grade).

1.2 The values stated in SI units are to be regarded as the standard. The values given in parentheses are for information only.

1.3 For specific hazard information and guidance, see the supplier's Material Safety Data Sheet for material listed in this specification.

1.4 The following applies to all specified limits in this standard; for purposes of determining conformance with this standard, an observed value or a calculated value shall be rounded off "to the nearest unit" in the last right-hand digit used in expressing the specification limit, in accordance with the rounding-off method of Practice E 29.

¹ This specification is under the jurisdiction of ASTM Committee D-1 D01 on Paint and Related Coatings, Materials, and Applications and is the direct responsibility of Subcommittee D01.35 on Solvents, Plasticizers, and Chemical Intermediates .

Current edition approved Oct. 10, 1998, 1, 2003. Published December 1998. Originally published as D 1718 – 60 T, approved in 1960. Last previous edition D 1718 – 90(1994)^{ε1}, approved in 1998 as D 1718 – 98.

***A Summary of Changes section appears at the end of this standard.**