



Designation: D 1725 — 62 (Reapproved 1996)^{ε1} — 04

Standard Test Method for Viscosity of Resin Solutions¹

This standard is issued under the fixed designation D 1725; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

^{ε1} NOTE — Editorial changes were made throughout in November 1996.

1. Scope

1.1 This test method covers the measurement of the viscosity of resin solutions.

1.2 The values stated in ~~inch-pound~~ SI units are to be regarded as the standard. The values given in parentheses are for information only.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use. For specific hazard statements, see Section 7.*

¹ This test method is under the jurisdiction of ASTM Committee ~~D-1~~ D01 on Paint and Related Coatings, Materials, and Applications and is the direct responsibility of Subcommittee D01.33 on Polymers and Resins.

Current edition ~~accepted Sept. 28, 1962~~: approved Mar. 1, 2004. Published March 2004. Originally ~~issued~~ approved in 1960. Replaces D 1725 — 60 ~~T~~. Last previous edition approved in 1962 as D 1725 — 62 (1996)^{ε1}.