



Designation: D2161 – 19

Standard Practice for Conversion of Kinematic Viscosity to Saybolt Universal Viscosity or to Saybolt Furol Viscosity¹

This standard is issued under the fixed designation D2161; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the U.S. Department of Defense.

1. Scope*

1.1 This practice² covers the conversion tables and equations for converting kinematic viscosity in mm^2/s at any temperature to Saybolt Universal viscosity in Saybolt Universal seconds (SUS) at the same temperature and for converting kinematic viscosity in mm^2/s at 122 °F and 210 °F (50 °C and 98.9 °C) to Saybolt Furol viscosity in Saybolt Furol seconds (SFS) at the same temperatures. Kinematic viscosity values are based on water being 1.0034 mm^2/s (cSt) at 68 °F (20 °C).

1.2 If a method other than Test Method D445 is used to generate the kinematic viscosity data, apply appropriate relative-bias correction factors as found in the precision section of that method, before performing the calculations of this practice.

NOTE 1—The equations in D2161 were originally empirically derived using data from both D445 and the Saybolt viscometer method. Therefore, it is conceivable that an error could result if the kinematic viscosities used are not bias-corrected to D445 results. It is recommended that kinematic viscosity be reported in millimetres squared per second, instead of Saybolt Universal Seconds (SUS) or Saybolt Furol Seconds (SFS). This method is being retained for the purpose of calculation of kinematic viscosities from SUS and SFS data that appear in past literature. One millimetre squared per second (mm^2/s) equals one centistoke (cSt), which is another unit commonly found in older literature.

1.3 The values stated in SI units are to be regarded as the standard. The values given in parentheses are provided for reference information purposes only. The SI unit of kinematic viscosity is mm^2/s .

1.3.1 *Exception*—Fahrenheit temperature units are used in this practice because they are accepted by industry for the type of legacy conversions described in this practice.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appro-*

priate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.

1.5 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 ASTM Standards:³

D445 Test Method for Kinematic Viscosity of Transparent and Opaque Liquids (and Calculation of Dynamic Viscosity)

D2270 Practice for Calculating Viscosity Index from Kinematic Viscosity at 40 °C and 100 °C

D7042 Test Method for Dynamic Viscosity and Density of Liquids by Stabinger Viscometer (and the Calculation of Kinematic Viscosity)

2.2 ASTM Adjunct:⁴

ADJD2161 Viscosity Extrapolation Tables to Zero Degrees Fahrenheit (SSU)

3. Summary of Practice

3.1 The Saybolt Universal viscosity equivalent to a given kinematic viscosity varies with the temperature at which the determination is made. The basic conversion values are those given in Table 1 for 100 °F. The Saybolt Universal viscosity equivalent to a given kinematic viscosity at any temperature may be calculated as described in 4.3. Equivalent values at 210 °F are given in Table 1 for convenience.

3.2 The Saybolt Furol viscosity equivalents are tabulated in Table 3 for temperatures of 122 °F and 210 °F only.

3.3 Examples for using the tables are given in Appendix X1.

¹ This practice is under the jurisdiction of ASTM Committee D02 on Petroleum Products, Liquid Fuels, and Lubricants and is the direct responsibility of Subcommittee D02.07 on Flow Properties.

Current edition approved May 1, 2019. Published May 2019. Originally approved in 1963, replacing former D446 and D666. Last previous edition approved in 2017 as D2161 – 17. DOI: 10.1520/D2161-19.

² This practice, together with Practice D2270, replaces Compilation of ASTM Viscosity Tables for Kinematic Viscosity Conversions.

³ For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

⁴ Available from ASTM International Headquarters. Order Adjunct No. ADJD2161. Original adjunct produced in 1998.

*A Summary of Changes section appears at the end of this standard