Designation: D2270 – 10$^{\varepsilon 1}$

British Standard 4459

Designation: 226/91 (95)

# Standard Practice for Calculating Viscosity Index from Kinematic Viscosity at 40 and 100°C[1]

This standard is issued under the fixed designation D2270; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

*This standard has been approved for use by agencies of the Department of Defense.*

ε[1] NOTE—Corrected equation references in 5.2.4.2 editorially in March 2011.

## 1. Scope*

1.1 This practice[2] covers the procedures for calculating the viscosity index of petroleum products, such as lubricating oils, and related materials from their kinematic viscosities at 40 and 100°C.

NOTE 1—The results obtained from the calculation of *VI* from kinematic viscosities determined at 40 and 100°C are virtually the same as those obtained from the former *VI* system using kinematic viscosities determined at 37.78 and 98.89°C.

1.2 This practice does not apply to petroleum products with kinematic viscosities less than 2.0 mm$^2$/s at 100°C. Table 1 given in this practice applies to petroleum products with kinematic viscosities between 2 and 70 mm$^2$/s at 100°C. Equations are provided for calculating viscosity index for petroleum products having kinematic viscosities above 70 mm$^2$/s at 100°C.

1.2.1 In cases where kinematic viscosity data are not available at temperatures of 40 and 100°C, an estimate may be made of the viscosity index by calculating the kinematic viscosity at temperatures of 40 and 100°C from data obtained at other temperatures. Such viscosity index data may be considered as suitable for information only and not for specification purposes. See Test Method D341, Annex A1.

1.3 The kinematic viscosity values are determined with reference to a value of 1.0034 mm$^2$/s at 20.00°C for distilled water. The determination of the kinematic viscosity of a petroleum product shall be carried out in accordance with Test Methods D445, D7042, IP 71, or ISO 3104.

1.3.1 If Viscosity Index calculated for a given sample using kinematic viscosity measurements from different test methods are in disagreement, the values calculated from Test Method D445 measurements shall be accepted.

1.4 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.4.1 The values stated in SI units are to be regarded as the standard. For user reference, 1 mm$^2$/s = 10$^{-6}$m$^2$/s = 1 cSt.

1.5 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

## 2. Referenced Documents

2.1 *ASTM Standards:*[3]

D341 Practice for Viscosity-Temperature Charts for Liquid Petroleum Products

D445 Test Method for Kinematic Viscosity of Transparent and Opaque Liquids (and Calculation of Dynamic Viscosity)

D1695 Terminology of Cellulose and Cellulose Derivatives

D7042 Test Method for Dynamic Viscosity and Density of Liquids by Stabinger Viscometer (and the Calculation of Kinematic Viscosity)

E29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications

2.2 *ISO Standards:*[4]

[1] This practice is under the jurisdiction of ASTM Committee D02 on Petroleum Products and Lubricants and is the direct responsibility of Subcommittee D02.07 on Flow Properties.

In the IP, this practice is under the jurisdiction of the Standardization Committee and issued under the fixed designation IP 226. The final number indicates the year of last revision.

Current edition approved Oct. 1, 2010. Published November 2010. Originally approved in 1964. Last previous edition approved in 2004 as D2270–04. DOI: 10.1520/D2270-10.

[2] Supporting data (Metrication of Viscosity Index System Method D2270) have been filed at ASTM International Headquarters and may be obtained by requesting Research Report RR:D02-1009.

[3] For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

[4] Available from American National Standards Institute (ANSI), 25 W. 43rd St., 4th Floor, New York, NY 10036.

***A Summary of Changes section appears at the end of this standard.**

Copyright. © ASTM International. 100 Barr Harbor Drive, P.O. Box C700 West Conshohocken, Pennsylvania 19428-2959, United States

Copyright by ASTM Int'l (all rights reserved); Mon Apr 18 08:42:14 EDT 2011
Downloaded/printed by
Julien Brosse (Normalab+Technologies) pursuant to License Agreement. No further reproductions authorized.