



Standard Specification for Refined Phthalic Anhydride-1308¹

This standard is issued under the fixed designation D 2403; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (€) indicates an editorial change since the last revision or reapproval.

€¹ NOTE—Section 1 was changed editorially in January 2003.

1. Scope

1.1 This specification covers refined phthalic anhydride-1308.

1.2 The following applies to all specified limits in this specification: for purposes of determining conformance with this specification, an observed value or a calculated value shall be rounded off “to the nearest unit” in the last right-hand digit used in expressing the specification limit, in accordance with the rounding-off method of Practice E 29.

1.3 Consult current OSHA regulations, supplier’s Material Safety Data Sheets, and local regulations regarding all material used in this specification.

2. Referenced Documents

2.1 ASTM Standards:

D 1493 Test Method for Solidification Point of Industrial Organic Chemicals²

D 3366 Test Method for Color of Maleic Anhydride and Phthalic Anhydride in the Molten State and After Heating (Platinum-Cobalt Scale)²

D 3438 Practice for Sampling and Handling Naphthalene, Maleic Anhydride, and Phthalic Anhydride²

E 29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications³

2.2 Other Document:

OSHA Regulations, 29 CFR, paragraphs 1910.1000 and 1910.1200⁴

3. Properties

3.1 Phthalic anhydride shall conform to the following requirements:

Property	Specification	Test Method
Solidification point, min, °C	130.8	D 1493
Molten color, max	30	D 3366
Molten color after heating, max	100	D 3366

4. Sampling

4.1 The material shall be sampled in accordance with Practice D 3438.

5. Keywords

5.1 color; phthalic anhydride; solidification point

¹ This specification is under the jurisdiction of ASTM Committee D16 on Aromatic Hydrocarbons and Related Chemicals and is the direct responsibility of Subcommittee D16.02 on Oxygenated Aromatics.

Current edition approved Jan. 10, 2003. Published March 2003. Originally approved in 1965. Last previous edition approved in 1996 as D 2403 – 96.

² Annual Book of ASTM Standards, Vol 06.04.

³ Annual Book of ASTM Standards, Vol 14.02.

⁴ Available from U.S. Government Printing Office Superintendent of Documents, 732 N. Capitol St., NW, Mail Stop: SDE, Washington, DC 20401.

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).