



Standard Test Method for Determination of C₂ through C₅ Hydrocarbons in Gasolines by Gas Chromatography¹

This standard is issued under the fixed designation D2427; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method covers the determination of the two (C₂) through five (C₅-) carbon paraffins and mono-olefins in gasolines. The concentrations by volume or mass (weight) of the following components are generally reported:

- 1.1.1 Ethylene plus ethane
- 1.1.2 Propane
- 1.1.3 Propylene
- 1.1.4 Isobutane
- 1.1.5 *n*-Butane
- 1.1.6 Butene-1 plus isobutylene
- 1.1.7 *trans*-Butene-2
- 1.1.8 *cis*-Butene-2
- 1.1.9 Isopentane
- 1.1.10 3-Methylbutene-1
- 1.1.11 *n*-Pentane
- 1.1.12 Pentene-1
- 1.1.13 2-Methylbutene-1
- 1.1.14 *trans*-Pentene-2
- 1.1.15 *cis*-Pentene-2
- 1.1.16 2-Methylbutene-2

1.2 This test method does not cover the determination of cyclic olefins, diolefins, or acetylenes. These are usually minor components in finished gasolines.

1.3 Samples to be analyzed should not contain significant amounts of material boiling lower than ethylene.

1.4 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.4.1 *Exception*—Alternative units, in common usage, are also provided to improve the clarity and aid the user of this test method.

1.5 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appro-*

priate safety and health practices and determine the applicability of regulatory limitations prior to use.

2. Referenced Documents

2.1 *ASTM Standards*:²

D2001 Test Method for Depentanization of Gasoline and Naphthas

3. Summary of Test Method

3.1 The sample is injected into a gas-liquid partition column. The components are separated as they pass through the column with an inert carrier gas and their presence in the effluent is detected and recorded as a chromatogram. Materials containing components having more than five carbon atoms can either be backflushed from the system without measurement, or recorded as a broad peak by reversing the direction of the carrier gas through the column at such time as to regroup the higher-boiling portion (C₆ and heavier) of the sample. If backflushing is used, the concentration of C₂ through C₅ hydrocarbons may be related to the whole sample by adding a known quantity of low-boiling internal standard to the sample prior to analysis. Alternatively, a known amount of sample can be charged and compared to a standard sample run under the same conditions. Sample composition is determined from the chromatogram by comparing peak areas with those obtained using known amounts of calibration standards or a synthetic blend.

4. Significance and Use

4.1 In hydrocarbon type analyses of gasolines, highly volatile fuels can need to be stabilized by depentanization (Test Method **D2001**) prior to analysis. A knowledge of the composition of light hydrocarbons in the overhead from the depentanization process is useful in converting analyses of the depentanized fraction to a total sample basis.

5. Apparatus

5.1 *Chromatograph*—Any chromatograph having a thermostated oven and a detection system of adequate sensitivity may

¹ This test method is under the jurisdiction of ASTM Committee D02 on Petroleum Products, Liquid Fuels, and Lubricants and is the direct responsibility of Subcommittee D02.04.0L on Gas Chromatography Methods.

Current edition approved Oct. 1, 2015. Published December 2015. Originally approved in 1965. Last previous edition approved in 2011 as D2427 – 06 (2011). DOI: 10.1520/D2427-06R15.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.