



Designation: D 2902 – 95a00

An American National Standard

Standard Specification for Fluoropolymer Resin Heat-Shrinkable Tubing for Electrical Insulation¹

This standard is issued under the fixed designation D 2902; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification applies to flexible heat-shrinkable extruded tubing made from tetrafluoroethylene resin, copolymer of tetrafluoroethylene and hexafluoropropylene, and from perfluoroalkoxy resin for use as electrical insulation.

NOTE 1—This standard is similar but not identical to IEC 60684–3–240 to –243.

1.2 The values stated in inch-pound units are to be regarded as the standard except temperature which shall be stated in degrees Celsius. Values in parentheses are for information only.

2. Referenced Documents

2.1 ASTM Standards:

C 618 Specification for Coal Fly Ash and Raw or Calcined Natural Pozzolan for Use as a Mineral Admixture in Portland Cement Concrete²

¹ This specification is under the jurisdiction of ASTM Committee D-9 D09 on Electrical and Electronic Insulating Materials and is the direct responsibility of Subcommittee D09.07 on Flexible and Rigid Insulating Materials.

Current edition approved Nov. 10, 1995; 2000. Published January 1996; July 2000. Originally published as D 2902 – 70 T. Last previous edition D 2902 – 95a.