This document is not an ASTM standard and is intended only to provide the user of an ASTM standard an indication of what changes have been made to the previous version. Because it may not be technically possible to adequately depict all changes accurately, ASTM recommends that users consult prior editions as appropriate. In all cases only the current version of the standard as published by ASTM is to be considered the official document.

Designation: D 3273 – ~~94~~00

Standard Test Method for Resistance to Growth of Mold on the Surface of Interior Coatings in an Environmental Chamber[1]

This standard is issued under the fixed designation D 3273; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the Department of Defense.

1. Scope

1.1 This test method describes a small environmental chamber and the conditions of operation to evaluate reproducibly in a 4-week period the relative resistance of paint films to surface mold fungi, mildew growth in a severe interior environment. The

[1] This test method is under the jurisdiction of ASTM Committee ~~D-1~~ D01 on Paint and Related Coatings, Materials, and Applications and is the direct responsibility of Subcommittee D01.28 on Biodeterioration.

Current edition approved ~~Aug. 15, 1994.~~ Nov. 10, 2000. Published ~~October 1994.~~ January 2001. Originally published as D 3273 – 73 T. Last previous edition ~~D 3273 – 86 (1991)$^{\epsilon 1}$~~. D 3273 – 94.

Copyright © ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States.