



Standard Test Method for Infiltration Rate of Soils in Field Using Double-Ring Infiltrometer¹

This standard is issued under the fixed designation D 3385; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the Department of Defense.

1. Scope

1.1 This test method describes a procedure for field measurement of the rate of infiltration of liquid (typically water) into soils using double-ring infiltrometer.

1.2 Soils should be regarded as natural occurring fine or coarse-grained soils or processed materials or mixtures of natural soils and processed materials, or other porous materials, and which are basically insoluble and are in accordance with requirements of 1.5.

1.3 This test method is particularly applicable to relatively uniform fine-grained soils, with an absence of very plastic (fat) clays and gravel-size particles and with moderate to low resistance to ring penetration.

1.4 This test method may be conducted at the ground surface or at given depths in pits, and on bare soil or with vegetation in place, depending on the conditions for which infiltration rates are desired. However, this test method cannot be conducted where the test surface is below the ground water table or perched water table.

1.5 This test method is difficult to use or the resultant data may be unreliable, or both, in very pervious or impervious soils (soils with a hydraulic conductivity greater than about 10^{-2} cm/s or less than about 1×10^{-6} cm/s) or in dry or stiff soils that most likely will fracture when the rings are installed. For soils with hydraulic conductivity less than 1×10^{-6} cm/s refer to Test Method D 5093.

1.6 This test method cannot be used directly to determine the hydraulic conductivity (coefficient of permeability) of the soil (see 5.2).

1.7 The values stated in SI units are to be regarded as the standard.

1.8 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 ASTM Standards:

D 653 Terminology Relating to Soil, Rock, and Contained Fluids²

D 1452 Practice for Soil Investigation and Sampling by Auger Borings²

D 2216 Method for Laboratory Determination of Water (Moisture) Content of Soil, Rock, and Soil-Aggregate Mixtures²

D 2488 Practice for Description and Identification of Soils (Visual-Manual Procedure)²

D 5093 Test Method for Field Measurement of Infiltration Rate Using a Double-Ring Infiltrometer With a Sealed Inner Ring²

3. Terminology

3.1 Definitions:

3.1.1 *incremental infiltration velocity*—the quantity of flow per unit area over an increment of time. It has the same units as the infiltration rate.

3.1.2 *infiltration*—the downward entry of liquid into the soil.

3.1.3 *infiltration rate*—a selected rate, based on measured incremental infiltration velocities, at which liquid can enter the soil under specified conditions, including the presence of an excess of liquid. It has the dimensions of velocity (that is, $\text{cm}^3 \text{cm}^{-2} \text{h}^{-1} = \text{cm h}^{-1}$).

3.1.4 *infiltrometer*—a device for measuring the rate of entry of liquid into a porous body, for example, water into soil.

3.1.5 For definitions of other terms used in this test method, refer to Terminology D 653.

4. Summary of Test Method

4.1 The double-ring infiltrometer method consists of driving two open cylinders, one inside the other, into the ground, partially filling the rings with water or other liquid, and then maintaining the liquid at a constant level. The volume of liquid added to the inner ring, to maintain the liquid level constant is the measure of the volume of liquid that infiltrates the soil. The

¹ This test method is under the jurisdiction of ASTM Committee D18 on Soil and Rock and is the direct responsibility of Subcommittee D18.04 on Hydrologic Properties of Soil and Rock.

Current edition approved June 10, 2003. Published August 2003. Originally approved in 1975. Discontinued December 2002 and reinstated as D 3385 – 03.

² *Annual Book of ASTM Standards*, Vol 04.08.