



Designation: D3574 – 16

Standard Test Methods for Flexible Cellular Materials—Slab, Bonded, and Molded Urethane Foams¹

This standard is issued under the fixed designation D3574; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the U.S. Department of Defense.

1. Scope*

1.1 These test methods apply to slab, bonded, and molded flexible cellular products known as urethane foams. Urethane foam is generally defined as an expanded cellular product produced by the interaction of active hydrogen compounds, water, and isocyanates.

1.2 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

1.3 The values stated in SI units are to be regarded as standard.

NOTE 1—There is no known ISO equivalent to this standard, however certain test methods in this standard have similar or equivalent ISO standards and are listed in the scope of the individual test method sections.

2. Referenced Documents

2.1 ASTM Standards:²

D412 Test Methods for Vulcanized Rubber and Thermoplastic Elastomers—Tension

D624 Test Method for Tear Strength of Conventional Vulcanized Rubber and Thermoplastic Elastomers

D737 Test Method for Air Permeability of Textile Fabrics

D3576 Test Method for Cell Size of Rigid Cellular Plastics

D3675 Test Method for Surface Flammability of Flexible Cellular Materials Using a Radiant Heat Energy Source

E162 Test Method for Surface Flammability of Materials Using a Radiant Heat Energy Source

E662 Test Method for Specific Optical Density of Smoke Generated by Solid Materials

¹ These test methods are under the jurisdiction of ASTM Committee D20 on Plastics and are the direct responsibility of Subcommittee D20.22 on Cellular Materials - Plastics and Elastomers.

Current edition approved Nov. 1, 2016. Published January 2017. Originally approved in 1977. Last previous edition approved in 2011 as D3574 – 11. DOI: 10.1520/D3574-16.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

E691 Practice for Conducting an Interlaboratory Study to Determine the Precision of a Test Method

3. Terminology

3.1 Definitions of Terms Specific to This Standard:

3.1.1 **bonded foam**—a product produced by the adhesion of small pieces of urethane foam to each other with a suitable bonding agent.

3.1.2 **core**—the internal portion of a molded part, free of skin.

3.1.3 **cored foam**—a flexible cellular material containing a multiplicity of holes (usually, but not necessarily, cylindrical in shape), molded or cut into the material in some pattern, normally perpendicular to the foam rise direction, and extending part or all the way through the piece.

3.1.4 **convoluted foam**—a flexible cellular material specially cut into sheets with “egg carton”-like dimples. The dimple peaks and bases can have varied shapes and dimensions.

3.1.5 **flexible cellular product**—a cellular organic polymeric material that will not rupture when a specimen 200 by 25 by 25 mm is bent around a 25-mm diameter mandrel at a uniform rate of one lap in 5 s at a temperature between 18 and 29°C.

3.1.6 **molded foam**—a cellular product having the shape of the enclosed chamber in which it is produced by foaming.

3.1.7 **skin**—the smooth surface layer of a molded foam product, formed by contact with the mold or surfaces.

3.1.8 **slab**—a section of foam that is cut from the internal portion of a large bun.

3.1.9 **urethane foam**—a flexible cellular product produced by the interaction of active hydrogen compounds, water, and isocyanates.

3.1.10 **viscoelastic foam**—a specially formulated urethane foam characterized by having slow recovery, low resilience, and high hysteresis loss.

3.1.11 **cell count**—a measurement used to characterize different types of foams based on the size of the individual cells in the foam matrix, typically expressed as either average cell diameter or as the number of cells per linear distance. For measuring cell counts, see Test Method **D3576**.

*A Summary of Changes section appears at the end of this standard