



Designation: D 3676 – 96a01

Standard Specification for Rubber Cellular Cushion Used for Carpet or Rug Underlay¹

This standard is issued under the fixed designation D 3676; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope*

1.1 This specification covers high-density cellular rubber adhered to carpet, rugs, or various substrates for use as separate underlay.

NOTE 1—This underlay. This standard may also be used as a specification ~~does not cover~~ for separately blown sponge used as carpet underlay.

1.2 This specification provides material and dimensional requirements and test methods for specific properties of compression set, compression resistance, delamination strength, and accelerated aging.

NOTE 2~~1~~—This specification does not include requirements for burning characteristics. It ~~should~~ shall be noted that Flammable Fabrics Act Regulations

¹ This specification is under the jurisdiction of ASTM Committee D20 on Plastics and is the direct responsibility of Subcommittee D20.22 on Cellular Materials-Plastics and Elastomers.

Current edition approved ~~July~~ November 10, 1996; 2001. Published ~~February 1997~~ January 2002. Originally published as D 3676 – 78. Last previous edition ~~D 3676 – 96~~. This edition includes the addition of an ISO equivalency statement, ~~crosshead speed for the compression resistance test, modified recovery time in the compression set test, and keywords: D 3676 – 96a.~~

*A Summary of Changes section appears at the end of this standard.