



Standard Performance Specification for Woven, Lace, and Knit Household Curtain and Drapery Fabrics¹

This standard is issued under the fixed designation D 3691; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the Department of Defense.

1. Scope

1.1 This performance specification covers the requirements for all knit, lace, foam back, stitch-bonded, conventional weights, and sheer woven fabrics to be used in the manufacture of curtains and draperies.

1.2 This performance specification is applicable to all fabrics except those made of glass.

1.3 For those properties where fabric direction is pertinent, these requirements apply to the length and width directions for woven fabric and to both the wale and course directions for knit fabric.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 ASTM Standards:

- D 123 Terminology Relating to Textiles²
- D 231 Methods of Testing Tolerances for Knit Goods³
- D 1336 Test Method for Distortion of Yarn in Woven Fabrics²
- D 1424 Test Method for Tearing Strength of Woven Fabrics by Falling-Pendulum (Elemendorf) Apparatus²
- D 2261 Test Method for Tearing Strength of Fabrics by the Tongue (Single Rip) Procedure (Constant-Rate-of-Extension Tensile Testing Machine)²
- D 2724 Test Methods for Bonded, Fused, and Laminated Apparel Fabrics²
- D 2905 Practice for Statements on Number of Specimens for Textiles²
- D 5034 Test Method for Breaking Strength and Elongation of Textile Fabrics (Grab Test)²

2.2 AATCC Test Methods⁴

- 8 Colorfastness to Crocking: AATCC Crockmeter Method
- 16 Colorfastness to Light
- 23 Colorfastness to Burnt Gas Fumes
- 61 Colorfastness to Laundering Home and Commercial: Accelerated
- 116 Colorfastness to Crocking: Rotary Vertical Crockmeter Method
- 124 Appearance of Fabrics After Repeated Home Laundering
- 129 Colorfastness to Ozone in the Atmosphere Under High Humidities
- 132 Colorfastness to Dry Cleaning
- 135 Dimensional Changes in Automatic Home Laundering of Durable Press Woven or Knit Fabric
- 172 Colorfastness to Non-Chlorine Bleach in Home Laundering
- 187 Dimensional Changes of Fabrics: Accelerated
- 188 Colorfastness to Sodium Hyperchlorite Bleach in Home Laundering
- Evaluation Procedure 1 Gray Scale for Color Change
- Evaluation Procedure 2 Gray Scale for Staining
- Evaluation Procedure 9 Visual Assessment of Color Difference of Textiles

NOTE 1—Reference to test methods in this specification give only the permanent part of the designation of ASTM, AATCC, or other test methods. The current editions of each test method cited shall prevail.

3. Terminology

3.1 Definitions:

3.2 For definitions of other textile terms used in this specification, refer to Terminology D 123 and to the Technical Manual of the American Association of Textile Chemists and Colorists.⁴

4. Significance and Use

4.1 Fabrics intended for this end-use should meet all of the requirements listed in Table 1.

4.2 It should be recognized that fabric can be produced

¹ This specification is under the jurisdiction of ASTM Committee D13 on Textiles and is the direct responsibility of Subcommittee D13.63 on Home Furnishings.

Current edition approved April 10, 2002. Published July 2002. Originally published as D 3691 – 78. Last previous edition D 3691 – 95a(2001).

² Annual Book of ASTM Standards, Vol 07.02.

³ Discontinued—See 1979 Annual Book of ASTM Standards, Part 32.

⁴ Available from American Association of Textile Chemists and Colorists, P.O. Box 12215, Research Triangle Park, NC 27709.