



Designation: D 3734 – 9601

Standard Specification for High-Flash Aromatic Naphthas¹

This standard is issued under the fixed designation D 3734; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope*

1.1 This specification covers two types of aromatic hydrocarbon solvents, normally petroleum distillates, having high flash points, moderately low volatility, and a distillation range of approximately 50°F (30°C). These solvents are used primarily by the coatings industry and are commonly referred to as high-flash aromatic naphthas.

1.2 For specific hazard information and guidance, see the supplier's Material Safety Data Sheet for materials listed in this specification.

2. Referenced Documents

2.1 ASTM Standards:

¹ This specification is under the jurisdiction of ASTM Committee D-1 D01 on Paint and Related Coatings, Materials, and Applications and is the direct responsibility of Subcommittee D01.35 on Solvents, Plasticizers, and Chemical Intermediates.

Current edition approved Jan. 10, 1996; 2001. Published March 1996; July 2001. Originally published as D 3734 – 78. Last previous edition D 3734 – 94.

*A Summary of Changes section appears at the end of this standard.