



Designation: D 3960 – 01

Standard Practice for Determining Volatile Organic Compound (VOC) Content of Paints and Related Coatings¹

This standard is issued under the fixed designation D 3960; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the Department of Defense.

1. Scope

1.1 This practice measures the volatile organic compound (VOC) content of solventborne and waterborne paints and related coatings as determined from the quantity of material released from a sample under specified bake conditions and subtracting exempt volatile compounds and water if present.

NOTE 1—The regulatory definition, under the control of the U.S. EPA, can change. To ensure currency, contact the local air pollution control agency.

1.2 This practice provides a guide to the selection of appropriate ASTM test methods for the determination of VOC content.

1.3 Certain organic compounds that may be released under the specified bake conditions are not classified as VOC as they do not participate in atmospheric photochemical reactions. Such nonphotochemically reactive compounds are referred to as exempt volatile compounds in this practice.

NOTE 2—A list of the current US EPA approved exempt volatile compounds is found in Appendix Appendix X3, paragraph X3.1.1.1.

1.4 VOC content is calculated as a function of (1) the volume of coating less water and exempt volatile compounds, and (2) the volume of coating solids, and (3) the weight of coating solids.

2. Referenced Documents

2.1 ASTM Standards:

- D 1475 Test Method for Density of Paint, Varnish, Lacquer, and Related Products²
- D 2369 Test Method for Volatile Content of Coatings²
- D 2697 Test Method for Volume Nonvolatile Matter in Clear or Pigmented Coatings²
- D 2832 Guide for Determining Volatile and Nonvolatile Content of Paint and Related Coatings²
- D 3792 Test Method for Water Content of Water Reducible Paints by Direct Injection into a Gas Chromatograph²

¹ This practice is under the jurisdiction of ASTM Committee D01 on Paint and Related Coatings, Materials, and Applications and is the direct responsibility of Subcommittee D01.21 on Chemical Analysis of Paints and Paint Materials.

Current edition approved Jan. 10, 2001. Published March 2001. Originally published as D 3960 – 81. Last previous edition D 3960 – 98.

² *Annual Book of ASTM Standards*, Vol 06.01.

D 3925 Practice for Sampling Liquid Paints and Related Pigmented Coatings²

D 4017 Test Method for Water in Paints and Paint Materials by Karl Fischer Method²

D 4457 Test Method for Determination of Dichloromethane and 1,1,1-Trichloroethane in Paints and Coatings by Direct Injection into a Gas Chromatograph²

D 5095 Test Method for Determination of the Nonvolatile Content in Silanes, Siloxanes and Silane-Siloxane Blends Used in Masonry Water Repellent Treatments³

D 5201 Practice for Calculating Formulation Physical Constants of Liquid Paints and Coatings²

D 5403 Test Methods for Volatile Content of Radiation Curable Materials³

D 6093 Test Method for Percent Volume Nonvolatile Matter in Clear or Pigmented Coatings Using a Helium Gas Pycnometer²

D 6133 Test Method for Acetone Content of Solvent-Reducible and Water-Reducible Paints, Coatings, Resins, and Raw Materials by Direct Injection into a Gas Chromatograph²

E 180 Practice for Determining the Precision of ASTM Methods for Analysis and Testing of Industrial Chemicals⁴

2.2 Other Documents:

EPA Federal Reference Method 24—Determination of Volatile Matter Content, Density, Volume Solids, and Weight Solids of Surface Coatings⁵

EPA 450/3-84-019, U.S. Environmental Protection Agency Procedures for Certifying Quantity of Organic Compound Emitted by Paint, Ink, and Other Coatings⁵

EPA 450/3-83-013R, U.S. Environmental Protection Agency Glossary for Air Pollution Control of Industrial Coatings Operations⁵

3. Terminology

3.1 Definitions:

3.1.1 *exempt volatile compound*—organic compounds that

³ *Annual Book of ASTM Standards*, Vol 06.02.

⁴ *Annual Book of ASTM Standards*, Vol 15.05.

⁵ Available from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.