



Designation: D 3980 – 87

H-09-76

AMERICAN SOCIETY FOR TESTING AND MATERIALS
1916 Race St., Philadelphia, Pa. 19103
Reprinted from the Annual Book of ASTM Standards, Copyright ASTM
If not listed in the current combined index, will appear in the next edition.

Standard Practice for Interlaboratory Testing of Paint and Related Materials¹

This standard is issued under the fixed designation D 3980; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reappraisal. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reappraisal.

1. Scope

1.1 This practice covers the interlaboratory testing of paint and related materials. The information presented is intended to assist task groups in the effective planning of round-robin test programs.

1.2 The various parts appear in the following order:

	Sections
Part A—Definitions	3
Part B—Planning	4 to 11
Part C—Statistical Analysis	12 to 16
Part D—Analysis Presentation	17 to 20

1.3 This practice, in spite of its length, is not intended to cover all aspects of statistical design and analysis. For example, the analysis of variance used in the practice as the basis for estimating the precision is abridged in comparison to that normally used for establishing the significance of experimental factors. The publications listed in the appendix should be consulted for further information or explanations. For convenience, comparable practices developed by other ASTM technical committees are also shown.

2. Referenced Documents

2.1 ASTM Standards:

D 968 Test Methods for Abrasion Resistance of Organic Coatings by the Falling Abrasive Tester²

D 3793 Test Method for Low-Temperature Coalescence of Latex Paint Films²

E 180 Practice for Determining the Precision of ASTM Methods for Analysis and Testing of Industrial Chemicals³

PART A—DEFINITIONS

3. Definitions

3.1 The statistical terms used in this practice are defined, as nearly as possible, in every day language. For convenience, the terms are listed in order of use in the Practice.

3.2 *experimental design*—the complete plan for conducting an investigation or an interlaboratory study of materials, processes, or test methods. It is conveniently set forth in the form of a single comprehensive table showing number of laboratories, materials to be tested, test methods, number of operators, testing conditions, time of testing, and

degree of replication and repetition. The experimental design should provide the basis for an efficient statistical analysis of the results (see Part B, Planning).

3.3 *runs*—multiple chemical or physical determinations on the same specimen or physical measurements on the same panel made at the same time or within a very short time interval. Two such determinations are called duplicates. The individual results are not suitable for establishing precision but are used to ensure that a gross error has not occurred in one of the measurements.

3.4 *replicates*—multiple physical measurements on the same panel or chemical measurements made at different times, or physical measurements made on different panels, different areas of large structures, or different specimens of a liquid sample, within a short time interval to establish the precision of a method. In most cases the measurements are the mean of the runs as defined in 3.3.

3.5 *population*—the totality of observations on or determinations of a certain property or component obtained by the same procedure; theoretically, an infinite collection of measurements on a given item of interest but, practically, a large number of measurements of the item. Thus, when statistical procedures are used to determine whether or not two (or more) materials or test methods differ significantly with respect to some measurable property, in effect, the determination is whether these materials belong to the same or to different populations.

3.6 *sample*—a randomly selected subset of a population intended to be representative of it so as to enable obtaining an estimate of the property or composition of the entire population. The reliability of such an estimate can be expressed in terms of confidence limits (see 3.19). Through tests of significance (see 3.21), it is possible to state, with a specified degree of confidence, whether two or more samples are drawn from the same or from different populations.

3.7 *average*—a typical numerical value that attempts to summarize or reflect the location of a group of observations by a single number. While it is a measure of central tendency, it does not provide information on the variability of the individual observations. The following are different types of averages: arithmetic mean, weighted mean, algebraic mean, geometric mean, harmonic mean, median, and mode.

3.7.1 *mean (arithmetic)*—the value obtained by dividing the sum of a set of observations or results by their number. This value is an estimate of the mean of the parent population. Although the arithmetic mean is affected by extreme values and therefore may not be typical, it is amenable to statistical treatment and is the most commonly used average.

3.7.2 *median*—the central observation in an ordered set that contains an odd number of observations or the mean of

¹ This practice is under the jurisdiction of ASTM Committee D-1 on Paint and Related Coatings and Materials and is the direct responsibility of Subcommittee D01.20 on Sampling, Statistics, etc.

Current edition approved Nov. 27, 1987. Published January 1988. Originally published as D 3980 – 81. Last previous edition D 3980 – 86.

² Annual Book of ASTM Standards, Vol 06.01.

³ Annual Book of ASTM Standards, Vol 15.05.