



Standard Specification for Vapor-Degreasing Grade Perchloroethylene¹

This standard is issued under the fixed designation D 4376; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope *

1.1 This specification covers vapor-degreasing grade perchloroethylene.²

NOTE 1—Practices D 3844 and D 4276, and provide additional important information on solvent properties.

2. Referenced Documents

2.1 ASTM Standards:

D 1078 Test Method for Distillation Range of Volatile Organic Liquids³

D 2108 Test Method for Color of Halogenated Organic Solvents and Their Admixtures (Platinum-Cobalt Scale)⁴

D 2109 Test Methods for Nonvolatile Matter in Halogenated Organic Solvents and Their Admixtures⁴

D 2111 Test Methods for Specific Gravity of Halogenated Organic Solvents and Their Admixtures⁴

D 2942 Test Method for Total Acid Acceptance of Halogenated Organic Solvents (Nonreflux Method)⁴

D 2988 Test Method for Water-Soluble Halide Ion in Halogenated Organic Solvents and Their Admixtures⁴

D 2989 Test Method for Acidity-Alkalinity of Halogenated Organic Solvents and Their Admixtures⁴

D 3316 Test Method for Stability of Perchloroethylene with Copper⁴

D 3401 Test Method for Water in Halogenated Organic Solvents and Their Admixtures⁴

D 3741 Test Method for Appearance of Admixtures Containing Halogenated Organic Solvents⁴

D 3844 Practice for Labeling Halogenated Hydrocarbon Solvent Containers⁴

D 4276 Practice for Confined Area Entry⁴

2.2 Other Documents:

49 CFR 100 to 199 Department of Transportation Hazardous Materials Regulations⁵

29 CFR 1919.1200 Department of Labor, OSHA Regulations on Hazard Communications⁵

3. Properties

3.1 Vapor-degreasing grade perchloroethylene shall conform to the requirements prescribed in Table 1.

4. Packaging and Package Marking

4.1 Package and label industrial or commercial quantities in accordance with DOT regulations 49 CFR 100 to 199, and in accordance with state and local regulations, and with OSHA regulations found in 29 CFR 1910.1200.

5. Keywords

5.1 perchloroethylene; tetrachloroethylene; vapor degreasing

¹ This specification is under the jurisdiction of ASTM Committee D26 on Halogenated Organic Solvents and Fire Extinguishing Agents and is the direct responsibility of Subcommittee D26.02 on Vapor Degreasing.

Current edition approved Dec. 10, 2002. Published February 2003. Originally published in 1984. Last previous edition approved in 1998 as D 4376 – 98.

² Contains inhibitors.

³ Annual Book of ASTM Standards, Vol 06.04.

⁴ Annual Book of ASTM Standards, Vol 15.05.

⁵ The Code of Federal Regulations may be obtained from the Superintendent of Documents, US Government Printing Office, Washington, DC 20402.

