



Standard Test Method for Determining the In Situ Modulus of Deformation of Rock Mass Using the Flexible Plate Loading Method¹

This standard is issued under the fixed designation D 4395; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope*

1.1 This test method covers the preparation, equipment, test procedure, and data reduction for determining in situ modulus of deformation of a rock mass using the flexible plate loading method.

1.2 This test method is designed to be conducted in an adit or small underground chamber; however, with suitable modifications it could be conducted at the surface.

1.3 This test method is usually conducted parallel or perpendicular to the anticipated axis of thrust, as dictated by the design load.

1.4 Time-dependent tests not covered by this standard can be performed but are to be reported in another standard.

1.5 All observed and calculated values shall conform to the guidelines for significant digits and rounding established in Practice D 6026.

1.5.1 The method used to specify how data are collected, calculated, or recorded in this standard is not directly related to the accuracy to which the data can be applied in design or other uses, or both. How one applies the results obtained using this standard is beyond its scope.

1.6 The values stated in inch-pound units are to be regarded as the standard.

1.7 The references appended to this standard contain further information on this test method.

1.8 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.* For specific precaution statements, see Section 8.

2. Referenced Documents

2.1 ASTM Standards:²

D 653 Terminology Relating to Soil, Rock and Contained Fluids

D 2113 Practice for Diamond Core Drilling for Site Investigation

D 3740 Practice for Minimum Requirements for Agencies Engaged in the Testing and/or Inspection of Soil and Rock as Used in Engineering Design and Construction

D 4394 Test Method for Determining In Situ Modulus of Deformation of Rock Mass Using the Rigid Plate Loading Method

D 4403 Practice for Extensometers Used in Rock

D 4879 Guide for Geotechnical Mapping of Large Underground Openings in Rock

D 5079 Practices for Preserving and Transporting Rock Core Sample

D 5434 Guide for Field Logging of Subsurface Explorations of Soil and Rock

D 6026 Practice for Using Significant Digits in Geotechnical Data

D 6032 Test Method for Determining Rock Quality Designation (RQD) of Rock Core

3. Terminology

3.1 For terminology used in this test method, refer to Terminology D 653.

3.2 Definitions of Terms Specific to This Standard:

3.2.1 *deflection*—movement of the plate, mortar pad, or rock in response to and in the same direction as the applied load.

3.2.2 *flexible plate*—theoretically, a plate having no stiffness.

3.2.3 *load*—total force acting on the rock face.

¹ This test method is under the jurisdiction of ASTM Committee D18 on Soil and Rock and is the direct responsibility of Subcommittee D18.12 on Rock Mechanics.

Current edition approved Jan. 1, 2004. Published February 2004. Originally approved in 1984. Last previous edition approved in 1998 as D 4395 – 84 (1998).

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

