



Designation: D4727/D4727M – 22

Standard Specification for Corrugated and Solid Fiberboard Sheet Stock (Container Grade) and Cut Shapes¹

This standard is issued under the fixed designation D4727/D4727M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the U.S. Department of Defense.

1. Scope*

1.1 This specification covers fiberboard primarily used for the fabrication of boxes and interior details such as pads, sleeves, liners, partitions, die-cut sheets, etc.

1.2 The performance of fiberboard boxes is largely dependent on the paper components from which they are fabricated and, in the case of corrugated boxes, on the flute structure as well. Therefore, a variety of grades reflecting varied performance levels are specified.

1.3 The values stated in either inch-pound units or SI units are to be regarded separately as standard. Within the text, the SI units are shown in brackets. The values stated in each system are not exact equivalents; therefore, each system must be used independently of the other. Combining values from the two systems may result in non-conformance with the standard. See [IEEE/ASTM-SI-10](#) for conversion of units.

1.4 The following safety hazards caveat pertains only to the test portion, Sections 8 and 9, of this specification: *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.5 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

¹ This specification is under the jurisdiction of ASTM Committee D10 on Packaging and is the direct responsibility of Subcommittee D10.27 on Fiberboard Shipping Containers, Containerboard and Related Structures and Materials.

Current edition approved April 15, 2022. Published May 2022. Originally approved in 1987. Last previous edition approved in 2017 as D4727/D4727M – 17. DOI: 10.1520/D4727_D4727M-22.

2. Referenced Documents

2.1 ASTM Standards:²

D585 Practice for Sampling and Accepting a Single Lot of Paper, Paperboard, Fiberboard, and Related Product (Withdrawn 2010)³

D996 Terminology of Packaging and Distribution Environments

D1968 Terminology Relating to Paper and Paper Products

D3950 Specification for Strapping, Nonmetallic (and Joining Methods)

D3951 Practice for Commercial Packaging

D3953 Specification for Strapping, Flat Steel and Seals

D4169 Practice for Performance Testing of Shipping Containers and Systems

D4675 Guide for Selection and Use of Flat Strapping Materials¹

D5118/D5118M Practice for Fabrication of Fiberboard Shipping Boxes

D5168 Practice for Fabrication and Closure of Triple-Wall Corrugated Fiberboard Containers

D5639/D5639M Practice for Selection of Corrugated Fiberboard Materials and Box Construction Based on Performance Requirements

D6039/D6039M Specification for Open and Covered Wood Crates

D6199 Practice for Quality of Wood Members of Containers and Pallets

E162 Test Method for Surface Flammability of Materials Using a Radiant Heat Energy Source

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ The last approved version of this historical standard is referenced on www.astm.org.

*A Summary of Changes section appears at the end of this standard