



Designation: D 4811 – 9704

Standard Specification for Nonvulcanized (Uncured) Rubber Sheet Used as Roof Flashing¹

This standard is issued under the fixed designation D 4811; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification covers nonvulcanized (uncured) rubber sheet made of EPDM (ethylene-propylene-diene terpolymer) or CR (polychloroprene) intended for use as watertight roof flashing exposed to the weather.

1.2 The tests and property limits used to characterize these flashing materials are specific for each classification and are minimum values to make the product fit for its intended purpose.

1.3 SI units shall be used in referee decisions.

1.4 In-place roof system design criteria, such as fire resistance, field seaming strength, material compatibility, and uplift resistance, among others, are beyond the scope of this specification.

1.5 The following precautionary caveat pertains to the test methods portion only, Section 8, of this specification: *This standard may involve hazardous materials, operations, and equipment. This standard does not purport to address the safety concerns associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 ASTM Standards: ²

¹ This specification is under the jurisdiction of ASTM Committee D08 on Roofing, Waterproofing, Roofing and Bituminous Materials Waterproofing and is the direct responsibility of Subcommittee D08.18 on Nonbituminous Organic Roof Coverings.

Current edition approved June 10, 1997; Jan. 1, 2004. Published January 1998 2004. Originally published as D 4811 – 90; approved in 1990. Last previous edition approved in 1997 as D 4811 – 907.