



Designation: D 4866 – 88 (Reapproved ~~1997~~ 2003)^{ε1}

Standard Performance Specification for Coal Tar Pitch Emulsion Pavement Sealer Mix Formulations Containing Mineral Aggregates and Optional Polymeric Admixtures¹

This standard is issued under the fixed designation D 4866; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

^{ε1} NOTE—~~Editorial changes were made throughout.~~ The Referenced Documents section was editorially changed in ~~January 1997~~ July 2003.

1. Scope

1.1 This performance specification covers mixtures of emulsified coal-tar pitch (mineral colloid type), mineral aggregates, and optional polymeric admixtures that are used as a weather-protective and straight aliphatic hydrocarbon resistant coatings over bituminous pavements of airports, parking areas, and driveways.

1.2 The following safety hazards statement applies only to the test method portion, Section 6, of this specification: *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 ASTM Standards:

D 466 Test Methods for Films Deposited from Bituminous Emulsions²

¹ This specification is under the jurisdiction of ASTM Committee D08 on ~~Roofing, Waterproofing, Roofing and Bituminous Materials~~ Waterproofing and is the direct responsibility of Subcommittee D08.09 on Bituminous Emulsions.

Current edition approved ~~Dec. 15, 1988~~ July 10, 2003. Published ~~+~~ August 2003. Originally approved in 1988. Last previous edition approved in 1989 as D 4866 – 88.