



Designation: D4971 – 16

## Standard Test Method for Determining In Situ Modulus of Deformation of Rock Using Diametrically Loaded 76-mm (3-in.) Borehole Jack<sup>1</sup>

This standard is issued under the fixed designation D4971; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

### 1. Scope\*

1.1 This test method covers the estimation of in situ modulus of a rock mass at various depths and orientations. Information on time-dependent deformation may also be obtained.

1.2 This test method covers testing in an N size drill hole and is more relevant to a borehole jack device designed for “hard rock” than for soft rock.

1.3 All observed and calculated values shall conform to the guidelines for significant digits and rounding established in Practice D6026.

1.3.1 The method used to specify how data are collected, calculated, or recorded in this standard is not directly related to the accuracy to which the data can be applied in design or other uses, or both. How one applies the results obtained using this standard is beyond its scope.

1.4 The values stated in SI units are to be regarded as the standard. The values given in parentheses are mathematical conversions to inch-pound units that are provided for information only and are not considered standard.

1.5 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

### 2. Referenced Documents

2.1 *ASTM Standards:*<sup>2</sup>

D653 Terminology Relating to Soil, Rock, and Contained Fluids

D3740 Practice for Minimum Requirements for Agencies Engaged in Testing and/or Inspection of Soil and Rock as

Used in Engineering Design and Construction

D6026 Practice for Using Significant Digits in Geotechnical Data

D6032 Test Method for Determining Rock Quality Designation (RQD) of Rock Core

### 3. Terminology

3.1 *Definitions:*

3.1.1 For definitions of common technical terms in this standard, refer to Terminology D653.

3.2 *Definitions of Terms Specific to This Standard:*

3.2.1 *deformation, n*—change in shape or size, (see Terminology D653). In this test method deformation is the change in the diameter of the borehole.

3.2.2 *modulus of deformation, n*—ratio of stress to strain for a material under given loading conditions; numerically equal to the slope of the tangent or the secant of the stress-strain curve.

3.2.2.1 *Discussion*—The use of the term modulus of elasticity is recommended for materials that deform in accordance with Hooke’s law, and the term modulus of deformation is recommended for materials that deform otherwise, (see Terminology D653). In this test method, the modulus of deformation is calculated from the applied fluid pressure, the relative change in hole diameter, a function of Poisson’s ratio, and a constant.

3.2.3 *jack efficiency, n*—ratio of the jack plate pressure to the applied hydraulic pressure.

3.2.4 *hard rock borehole jack, n*—this refers to a specific borehole jack by the manufacture that has platens designed for harder rocks, goes to higher pressures than a soft rock borehole jack and whose displacement range is not exceeded at the maximum allowable pressure for the borehole jack.

### 4. Summary of Test Method

4.1 The drill logs for a drill hole to be tested are examined. Specific depths and orientations in the drill hole are selected based upon the objectives of the test program.

4.2 The borehole jack in the fully retracted position is positioned at each location selected in the drill hole for the test program. The 76 mm (3 in.) jacks, (see Fig. 1 and Fig. 2), induce unidirectional pressure to the walls of a borehole by means of two opposed curved steel platens each covering a 90°

<sup>1</sup> This test method is under the jurisdiction of ASTM Committee D18 on Soil and Rock and is the direct responsibility of Subcommittee D18.12 on Rock Mechanics. Current edition approved Dec. 1, 2016. Published January 2017. Originally approved in 1989. Last previous edition approved in 2008 as D4971 – 08. DOI: 10.1520/D4971-16.

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard’s Document Summary page on the ASTM website.

\*A Summary of Changes section appears at the end of this standard