



Designation: D5141 – 11 (Reapproved 2018)

Standard Test Method for Determining Filtering Efficiency and Flow Rate of the Filtration Component of a Sediment Retention Device¹

This standard is issued under the fixed designation D5141; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method is used to determine the filtering efficiency and the flow rate of the filtration component of a sediment retention device, such as a silt fence, silt barrier, or inlet protector.

1.1.1 The results are shown as a percentage for filtering efficiency and cubic metres per square metre per minute ($\text{m}^3/\text{m}^2/\text{min}$) or gallons per square foot per minute ($\text{gal}/\text{ft}^2/\text{min}$) for flow rate.

1.1.2 The filtering efficiency indicates the percent of sediment removed from sediment-laden water.

1.1.3 The flow rate is the average rate of passage of the sediment-laden water through the filtration component of a sediment retention device.

1.2 This test method requires several specialized pieces of equipment, such as an integrated water sampler and an analytical balance, or a vacuum filtration system. At the client's discretion, the test soil is either a site-specific soil or a soil that is representative of a target default gradation.

1.3 The values stated in SI units are the standard, while the inch-pound units are provided for information. The values expressed in each system may not be exact equivalents; therefore, each system must be used independently of the other, without combining values in any way.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.5 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

¹ This test method is under the jurisdiction of ASTM Committee D35 on Geosynthetics and is the direct responsibility of Subcommittee D35.03 on Permeability and Filtration.

Current edition approved Feb. 1, 2018. Published February 2018. Originally approved in 1991. Last previous edition approved in 2011 as D5141 – 11. DOI: 10.1520/D5141-11R18.

2. Referenced Documents

2.1 ASTM Standards:²

D123 Terminology Relating to Textiles

D653 Terminology Relating to Soil, Rock, and Contained Fluids

D4354 Practice for Sampling of Geosynthetics and Rolled Erosion Control Products (RECPs) for Testing

D4439 Terminology for Geosynthetics

D4759 Practice for Determining the Specification Conformance of Geosynthetics

2.2 American Public Health Association (APHA) Standard:³

208D Total Nonfiltrable Residue Dried at 103–105°C (Total Suspended Matter)

3. Terminology

3.1 Definitions:

3.1.1 *filter*—See Terminology D653.

3.1.2 *filtration component*—a geotextile or other material designed to act as a filter.

3.1.3 *geosynthetic, n*—a planar product manufactured from polymeric material used with foundation soil, rock, earth, or any other geotechnical engineering related material as an integral part of a man-made project, structure, or system. (See Practice D4759.)

3.1.4 *performance property, n*—a result obtained by conducting a performance test.

3.1.5 *performance test, n*—in geosynthetics, a laboratory procedure that simulates selected field conditions which can be used in design.

3.1.6 For definitions of other terms relating to geosynthetics, refer to Terminology D4439. For definitions of textile terms, refer to Terminology D123. For definitions of soil terms, refer to Terminology D653.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ Available from American Public Health Association (APHA), 1015 Eighteenth St. NW, Washington, DC 20036.