This document is not an ASTM standard and is intended only to provide the user of an ASTM standard an indication of what changes have been made to the previous version. Because it may not be technically possible to adequately depict all changes accurately, ASTM recommends that users consult prior editions as appropriate. In all cases only the current version of the standard as published by ASTM is to be considered the official document.

Designation: D 5162 – 0~~0~~1

Standard Practice for Discontinuity (Holiday) Testing of Nonconductive Protective Coating on Metallic Substrates[1]

This standard is issued under the fixed designation D 5162; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This practice covers procedures for determining discontinuities using two types of test equipment:

1.1.1 *Test Method A*—Low Voltage Wet Sponge, and

1.1.2 *Test Method B*—High Voltage Spark Testers.

[1] This practice is under the jurisdiction of ASTM Committee D~~-~~33 on Protective Coating and Lining Work for Power Generation Facilities and is the direct responsibility of Subcommittee D33.04 on Quality Systems and Inspection.

Current edition approved ~~May~~ June 10, 200~~0~~1. Published ~~July 2000.~~ August 2001. Originally published as D 5162 – 91. Last previous edition D 5162 –~~91~~ 00.

Copyright © ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States.