



Designation: D 5469 – 9300

Standard Guide for Application of New Spray Applied Polyurethane Foam and Coated Roofing Systems¹

This standard is issued under the fixed designation D 5469; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This guide covers the application of new roofing systems consisting of ~~sprayed~~ spray applied polyurethane foam insulation, elastomeric protective coatings, and optional mineral granules. This guide does not apply to retrofit or remedial applications.

1.2 Design criteria associated with the installation of ~~sprayed~~ spray in place polyurethane foam are beyond the scope of this specification.

1.3 The values stated in SI units are to be regarded as the standard. The values given in parentheses are for information only.

1.4 *This standard does not purport to address all of the safety ~~problems~~, concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 *ASTM Standards:*

C 1029 Specification for Spray-Applied Rigid Cellular Polyurethane Thermal Insulation²

¹ This guide is under the jurisdiction of ASTM Committee ~~D-8~~ D08 on Roofing, Waterproofing, and Bituminous Materials and is the direct responsibility of Subcommittee D08.06 on Spray Polyurethane Foam Roof Systems.

Current edition approved ~~Oct. 15, 1993~~, July 10, 2000. Published ~~September 1~~ September 1 2000. Originally published as D 5469 – 93. Last previous edition D 5469 – 93.