



Designation: D 5624 – 002

Standard Test Method for Determining the Transverse-Aggregate Spread Rate for Surface Treatment Applications¹

This standard is issued under the fixed designation D 5624; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method details the procedure for ~~calibrating~~ determining the ~~transverse-aggregate~~ aggregate spread rates in approximately 0.3–3-m (1–10-ft) transverse increments.

1.2 The values stated in SI units are to be regarded as standard. The inch-pound units shown in parentheses are for information only.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 *ASTM Standards:*

¹ This test method is under the jurisdiction of ASTM Committee D04 on Road and Paving Materials and is the direct responsibility of Subcommittee D04.24 on Bituminous Surface Treatments.

Current edition approved ~~July~~ Feb. 10, 2000~~2~~. Published ~~September 2000~~ April 2002. Originally published as D 5624–94. Last previous edition D 5624–~~94~~00.