



Designation: **D 5841 – 9500**

Standard Specification for Type III Polymer Modified Asphalt Cement for Use in Pavement Construction¹

This standard is issued under the fixed designation D 5841; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification covers asphalt cements that have been modified by the addition of the appropriate polymer for use in pavement construction. It was developed to provide a reference for specifying polymer modified asphalt and reflects the properties of currently available commercial products. The tests are intended to measure compatibility and degree of modification, not performance characteristics. This is not intended to be a performance based specification.

1.2 Type III polymer-modified asphalts are typically made with ethyl vinyl acetate. However any polymer may be used that will give the required test results when blended with the desired asphalt.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 ASTM Standards:

D 5 Test Method for Penetration of Bituminous Materials²

¹ This specification is under the jurisdiction of ASTM Committee D-4 D04 on Road and Paving Materials and is under the direct responsibility of Subcommittee D04.45 on Modified Asphalt Specifications.

Current edition approved Nov. Dec. 10, 1995; 2000. Published January 1996, February 2001. Originally published as D 5841-95. Last previous edition D 5841-95.