



Designation: D6074 – 15 (Reapproved 2022)

Standard Guide for Characterizing Hydrocarbon Lubricant Base Oils¹

This standard is issued under the fixed designation D6074; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This guide suggests physical, chemical, and toxicological test methods for characterizing hydrocarbon lubricant base oils derived from various refining processes including re-refining used oils and refining crude oil. This guide does not contain limits nor does it purport to cover all tests which could be employed; rather, it represents the first step in better describing important parameters of lubricant base oils affecting lubricant performance and safe handling. Tests have been identified to characterize the composition and performance of base oils in addition to verifying their consistency. Undesirable components have also been identified with a range of typical levels. These are not limits. It is the responsibility of the buyer and seller to determine and agree upon the implementation of this guide.

1.2 This guide applies only to base oils and not to finished lubricants.

1.3 Base oils containing detectable levels of esters, animal fats, vegetable oils, or other materials used as, or blended into, lubricants are not covered by this guide.

1.4 This guide is relevant to base oils composed of hydrocarbons and intended for use in formulating products including automotive and industrial lubricants. Although not intended to cover all base oil viscosity grades, this guide does cover the majority of viscosities that would be used in both automotive and industrial oil formulations. These base oils would typically have a viscosity of approximately 2 mm²/s to 40 mm²/s (cSt) at 100 °C (50 SUS to 3740 SUS at 100 °F).

1.5 The values stated in SI units are to be regarded as the standard. The values given in parentheses are for information only.

1.6 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

¹ This guide is under the jurisdiction of ASTM Committee D02 on Petroleum Products, Liquid Fuels, and Lubricants and is the direct responsibility of Subcommittee D02.P0 on Recycled Products.

Current edition approved Oct. 1, 2022. Published October 2022. Originally approved in 1998. Last previous edition approved in 2015 as D6074 – 15. DOI: 10.1520/D6074-15R22.

1.7 This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.

2. Referenced Documents

2.1 ASTM Standards:²

- D91 Test Method for Precipitation Number of Lubricating Oils
- D92 Test Method for Flash and Fire Points by Cleveland Open Cup Tester
- D93 Test Methods for Flash Point by Pensky-Martens Closed Cup Tester
- D97 Test Method for Pour Point of Petroleum Products
- D130 Test Method for Corrosiveness to Copper from Petroleum Products by Copper Strip Test
- D189 Test Method for Conradson Carbon Residue of Petroleum Products
- D287 Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method)
- D341 Practice for Viscosity-Temperature Equations and Charts for Liquid Petroleum or Hydrocarbon Products
- D445 Test Method for Kinematic Viscosity of Transparent and Opaque Liquids (and Calculation of Dynamic Viscosity)
- D524 Test Method for Ramsbottom Carbon Residue of Petroleum Products
- D664 Test Method for Acid Number of Petroleum Products by Potentiometric Titration
- D974 Test Method for Acid and Base Number by Color-Indicator Titration
- D1298 Test Method for Density, Relative Density, or API Gravity of Crude Petroleum and Liquid Petroleum Products by Hydrometer Method
- D1401 Test Method for Water Separability of Petroleum Oils and Synthetic Fluids
- D1500 Test Method for ASTM Color of Petroleum Products

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.