



Designation: D 6099 – 9703

Standard Test Method for Polyurethane Raw Materials: Determination of Acidity in Moderate to High Acidity Aromatic Isocyanates¹

This standard is issued under the fixed designation D 6099; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope*

1.1 This test method determines the acidity, expressed as parts per million (ppm) of HCl, in aromatic isocyanate samples of greater than 100-ppm acidity. The test method is applicable to products derived from toluene diisocyanate and methylene-*bis*-(4-phenylisocyanate) (see Note 1).

NOTE 1—~~This test method is no similar or equivalent to ISO standard 14898, Test Method A.~~

2. Referenced Documents

2.1 ASTM Standards:

¹ This test method is under the jurisdiction of ASTM Committee D-20 on Plastics and is the direct responsibility of Subcommittee D20.22 on Cellular Materials—Plastics and Elastomers.

Current edition approved April 10, 1997; 2003. Published in April 2003. Originally approved in 1997. Last previous edition approved in 1997 as D 6099 - 97.

*A Summary of Changes section appears at the end of this standard.