



Designation: D 6140 – 9700

Standard Test Method to Determine Asphalt Retention of Paving Fabrics Used in Asphalt Paving for Full-Width Applications¹

This standard is issued under the fixed designation D 6140; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method covers a procedure for determining the asphalt retention for paving fabrics. Paving fabrics are used in a fabric membrane interlayer system in pavements before the placement of an asphaltic overlay.

1.2 This test method shows the values in both SI units and inch-pound units. SI Units is the name for the system of metric units known as the International System of Units. Inch-pound units is the correct name for the customary units used in the United States. The values in inch-pound units are provided for information only.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 ASTM Standards:

¹ This test method is under the jurisdiction of ASTM Committee D-35 on Geosynthetics and is the direct responsibility of Subcommittee D35.03 on Permeability and Filtration.

Current edition approved May 10, 1997; 2000. Published September 2000. Originally published as D 6140-97. Last previous edition D 6140-97.