This document is not an ASTM standard and is intended only to provide the user of an ASTM standard an indication of what changes have been made to the previous version. Because it may not be technically possible to adequately depict all changes accurately, ASTM recommends that users consult prior editions as appropriate. In all cases only the current version of the standard as published by ASTM is to be considered the official document.

Designation: D 6182 – ~~97~~00

Standard Test Method for Flexibility and Adhesion of Finish on Leather[1]

This standard is issued under the fixed designation D 6182; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method is intended for use on finished leather to evaluate resistance to cracking, delamination, and discoloration of the finish when subjected to repeated flexing. This test method does not apply to wet blue.

1.2 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 *ASTM Standards:*

[1] This test method is under the jurisdiction of ASTM Committee D~~-~~31 on Leather and is the direct responsibility of Subcommittee D31.07 on Physical Properties—General .

Current edition approved ~~Oct.~~ Sept. 10, ~~1997.~~ 2000. Published ~~July 1998.~~ October 2000. Originally published as D 6182 – 97. Last previous edition D 6182 – 97.

Copyright © ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States.