



Designation: D 6221 – 9800

Standard Specification for Reinforced Bituminous Flashing Sheets for Roofing and Waterproofing¹

This standard is issued under the fixed designation D 6221; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification covers factory prepared reinforced bituminous sheet used in flashing. The bitumen used may be asphalt, coal-tar pitch, or polymer modified bitumen. The reinforcement may include any one or a combination of organic (wood fiber), polyester, or glass fiber felts, woven fabrics, or thermoplastic films. Fine mineral powders, granules, or metal foils may be used as surfacing.

1.2 The values stated in ~~inch-pound~~ SI units are to be regarded as standard. The ~~SI~~ inch-pound units shown in parentheses are for information only.

1.3 The following precautionary statement pertains only to the test method portion, Section 7, of this specification: *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 ASTM Standards:

D 228 Test Methods for Asphalt Roll Roofing, Cap Sheets, and Shingles²

¹ This specification is under the jurisdiction of ASTM Committee ~~D-8~~ D08 on Roofing, Waterproofing, and Bituminous Materials and is the direct responsibility of Subcommittee D08.04 on Felts and Fabrics.

Current edition approved ~~Feb. 10, 1998~~ June 10, 2000. Published ~~August 2000~~ Originally published as D 6221-98. Last previous edition D 6221-98.