



Standard Test Method for Testing Vertical Strip Drains in the Crimped Condition¹

This standard is issued under the fixed designation D6918; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

^{ε1} NOTE—Editorial changes were made throughout in March 2014.

1. Scope

1.1 This test method is a performance test that measures the effect crimping has on the ability of vertical strip drains to transmit water parallel to the plane of the drain.

1.2 This test method is applicable to all vertical strip drains.

1.3 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 *ASTM Standards:*²

D4354 Practice for Sampling of Geosynthetics and Rolled Erosion Control Products(RECPs) for Testing

D4439 Terminology for Geosynthetics

3. Terminology

3.1 *Definitions:*

3.1.1 For general geosynthetics terms used in this test method, refer to Terminology **D4439**.

3.2 *Definitions of Terms Specific to This Standard:*

3.2.1 *vertical strip drain, n*—a geocomposite consisting of a geotextile cover and drainage core installed vertically into soil to provide drainage for accelerated consolidation of soils.

4. Summary of Test Method

4.1 This test method presents two methods for determining the effect of a crimp forming in the vertical strip drain due the consolidation of soils around it in the field.

¹ This test method is under the jurisdiction of ASTM Committee **D35** on Geosynthetics and is the direct responsibility of Subcommittee **D35.03** on Permeability and Filtration.

Current edition approved Jan. 1, 2014. Published March 2014. Originally approved in 2003. Last previous edition approved in 2009 as D6918–09. DOI: 10.1520/D6918-09R14E01.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

4.1.1 A vertical strip drain is sealed in a waterproof membrane to prevent any water from escaping out through the geotextile during the test.

4.1.2 The sealed vertical strip drain is placed in the appropriate crimping device and water is allowed to pass through it under a constant head of water.

4.1.3 A crimp is placed on the specimen, and water allowed to pass through it under a constant head in the crimped condition.

4.1.4 The flow rate of water along the plane of the uncrimped vertical strip drain is compared to the flow rate in the crimped condition.

5. Significance and Use

5.1 This test method is considered satisfactory for the acceptance of commercial shipments of vertical strip drains.

5.1.1 In case of dispute arising from differences in reported test results when using this test method for acceptance testing of commercial shipments, the purchaser and the supplier should conduct comparative tests to determine if there is any statistical bias between their laboratories. Competent statistical assistance is recommended for the investigation of bias. As a minimum, the two parties should take a group of test specimens that as homogenous as possible, and that are from a lot of material of the type in question. The test specimens should be randomly assigned in numbers to each laboratory for testing. The average results from the two laboratories should be compared using Student's t-test for unpaired data and an acceptable probability level chosen by the two parties before the start of testing. If a bias is found, either its cause must be found and corrected, or the purchaser and the supplier must agree to interpret future test results in light of the known bias.

5.2 Vertical strip drains are installed in areas where it is desired to increase the rate of soil consolidation. It has been shown that as the soil around the vertical strip drain consolidates, a crimp may form in the vertical strip drain due to the movement of the drain in the area of soil consolidation.

5.3 This test method can be used to evaluate if there is any reduction in flow rate of water through the drain due to the crimping, and what effect, if any, this crimping may have on the rate of consolidation of the soil.