



Designation: D7014 – 22

Standard Practice for Installation of Double-Twisted Wire Mesh Gabions and Revet Mattresses¹

This standard is issued under the fixed designation D7014; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope*

1.1 This specification covers standard practice for foundation preparation, assembly, placement and filling of double-twisted wire mesh gabions and revet mattresses used for various erosion control, soil retention or freestanding structures.

1.2 This guide offers an organized collection of information or a series of options and does not recommend a specific course of action. This document cannot replace education or experience and should be used in conjunction with professional judgment. Not all aspects of this guide may be applicable in all circumstances. This ASTM standard is not intended to represent or replace the standard of care by which the adequacy of a given professional service must be judged, nor should this document be applied without consideration of a project's many unique aspects. The word "Standard" in the title of this document means only that the document has been approved through the ASTM consensus process."

1.3 *Units*—The values stated in SI units are to be regarded as standard. The values given in parentheses are provided for information only and are not considered standard.

1.4 *This standard may involve hazardous materials, operations, and equipment. This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.5 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

¹ This practice is under the jurisdiction of ASTM Committee D18 on Soil and Rock and is the direct responsibility of Subcommittee D18.25 on Erosion and Sediment Control Technology.

Current edition approved June 1, 2022. Published June 2022. Originally approved in 2004. Last previous edition approved in 2018 as D7014–18^{ε1}. DOI: 10.1520/D7014-22.

2. Referenced Documents

2.1 *ASTM Standards*:²

A975 Specification for Double-Twisted Hexagonal Mesh Gabions and Revet Mattresses (Metallic-Coated Steel Wire or Metallic-Coated Steel Wire With Poly(Vinyl Chloride) (PVC) Coating)

D653 Terminology Relating to Soil, Rock, and Contained Fluids

D6711 Practice for Specifying Rock to Fill Gabions, Revet Mattresses, and Gabion Mattresses

3. Terminology

3.1 *Definitions*:

3.1.1 For definitions of common technical terms in this standard, refer to Terminology D653.

3.2 *Definitions of Terms Specific to This Standard*:

3.2.1 *selvedge wire, n*—a terminal wire used to edge the wire mesh perpendicular to the double twist by mechanically wrapping the mesh wires around it at least 2.5 times or by inserting it through the twists and folding one mesh length.

3.2.2 *edge wire, n*—a terminal wire used to edge the wire mesh parallel to the double twist by continuously weaving it into the wire mesh.

3.2.3 *lacing wire, n*—for gabions and revet mattresses, a metallic coated steel wire or metallic coated steel wire with PVC coating used to assemble and interconnect empty units, to close and secure stone filled units and for internal stiffeners.

3.2.4 *fastener, n*—an alternate connector to lacing wire, used for binding operations for gabions and revet mattresses.

3.2.5 *stiffener, n*—for gabions, a length of metallic coated steel wire or metallic coated steel wire with PVC coating used for support of facing.

3.2.5.1 *Discussion*—Stiffeners can be formed at project site using lacing wire by connecting the front panel to the back panel of a gabion cell. Alternatively, preformed stiffeners can

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

*A Summary of Changes section appears at the end of this standard