



Designation: D7544 – 23

Standard Specification for Pyrolysis Liquid Biofuel¹

This standard is issued under the fixed designation D7544; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reappraisal. A superscript epsilon (ε) indicates an editorial change since the last revision or reappraisal.

1. Scope*

1.1 This specification covers grades of pyrolysis liquid biofuel produced from biomass intended for use in various types of fuel-burning equipment under various climatic and operating conditions. These grades are described as follows:

1.1.1 Grade G is intended for use in industrial burners equipped to handle the pyrolysis liquid biofuels meeting the requirements listed for Grade G in [Table 1](#). The pyrolysis liquid biofuel listed under Grade G in [Table 1](#) is not intended for use in residential heaters, small commercial boilers, engines, or marine applications.

1.1.2 Grade D is intended for use in commercial/industrial burners requiring lower solids and ash content and which are equipped to handle the pyrolysis liquid biofuels meeting the requirements listed for Grade D in [Table 1](#). The pyrolysis liquid biofuel listed under Grade D in [Table 1](#) is not intended for use in residential heaters, engines, or marine applications not modified to handle these types of fuels.

NOTE 1—For information on the significance of the physical, chemical, and performance properties identified in this specification, see [Appendix X1](#).

1.2 This specification is for use in contracts for the purchase of pyrolysis liquid biofuel and for guidance of consumers of this type of fuel.

1.3 Nothing in this specification should preclude observance of national or local regulations, which may be more restrictive.

NOTE 2—The generation and dissipation of static electricity may create problems in the handling of pyrolysis liquid biofuel. For more information on the subject, see [Guide D4865](#).

1.4 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.4.1 *Exception*—BTU units are included for information only in [3.2.3.1](#).

1.5 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the*

responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.

1.6 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 ASTM Standards:²

- [D93 Test Methods for Flash Point by Pensky-Martens Closed Cup Tester](#)
- [D97 Test Method for Pour Point of Petroleum Products](#)
- [D240 Test Method for Heat of Combustion of Liquid Hydrocarbon Fuels by Bomb Calorimeter](#)
- [D396 Specification for Fuel Oils](#)
- [D445 Test Method for Kinematic Viscosity of Transparent and Opaque Liquids \(and Calculation of Dynamic Viscosity\)](#)
- [D482 Test Method for Ash from Petroleum Products](#)
- [D4052 Test Method for Density, Relative Density, and API Gravity of Liquids by Digital Density Meter](#)
- [D4175 Terminology Relating to Petroleum Products, Liquid Fuels, and Lubricants](#)
- [D4294 Test Method for Sulfur in Petroleum and Petroleum Products by Energy Dispersive X-ray Fluorescence Spectrometry](#)
- [D4865 Guide for Generation and Dissipation of Static Electricity in Petroleum Fuel Systems](#)
- [D5854 Practice for Mixing and Handling of Liquid Samples of Petroleum and Petroleum Products](#)
- [D6469 Guide for Microbial Contamination in Fuels and Fuel Systems](#)
- [D7579 Test Method for Pyrolysis Solids Content in Pyrolysis Liquids by Filtration of Solids in Methanol](#)
- [E70 Test Method for pH of Aqueous Solutions With the Glass Electrode](#)

¹ This specification is under the jurisdiction of ASTM Committee [D02](#) on Petroleum Products, Liquid Fuels, and Lubricants and is the direct responsibility of Subcommittee [D02.E0](#) on Burner, Diesel and Non-Aviation Gas Turbine Fuels.

Current edition approved May 1, 2023. Published May 2023. Originally approved in 2009. Last previous edition approved in 2017 as D7544 – 12 (2017). DOI:10.1520/D7544-23.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

*A Summary of Changes section appears at the end of this standard