



Designation: D7968 – 17a

Standard Test Method for Determination of Polyfluorinated Compounds in Soil by Liquid Chromatography Tandem Mass Spectrometry (LC/ MS/MS)¹

This standard is issued under the fixed designation D7968; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This procedure covers the determination of selected polyfluorinated compounds (PFCs) in a soil matrix using solvent extraction, filtration, followed by liquid chromatography (LC) and detection with tandem mass spectrometry (MS/MS). These analytes are qualitatively and quantitatively determined by this method. This method adheres to multiple reaction monitoring (MRM) mass spectrometry. This procedure utilizes a quick extraction and is not intended to generate an exhaustive accounting of the content of PFCs in difficult soil matrices. An exhaustive extraction procedure for polyfluoroalkyl substances, such as published by Washington et al.,² for difficult matrices should be considered when analyzing PFCs.

1.2 *Units*—The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.3 The Method of Detection Limit³ and Reporting Range⁴ for the target analytes are listed in [Table 1](#).

1.3.1 The reporting limit in this test method is the minimum value below which data are documented as non-detects. Analyte detections between the method detection limit and the reporting limit are estimated concentrations and are not reported following this test method. In most cases, the reporting limit is calculated from the concentration of the Level 1

calibration standard as shown in [Table 2](#) for the polyfluorinated compounds after taking into account a 2-g sample weight and a final extract volume of 10 mL, 50 % water/50 % MeOH with 0.1 % acetic acid. The final extract volume is assumed to be 10 mL because 10 mL of 50 % water/50 % MeOH with 0.1 % acetic acid was added to each soil sample and only the liquid layer after extraction is filtered, leaving the solid and any residual solvent behind. It is raised above the Level 1 calibration concentration for PFOS, PFHxA, FHEA, and FOEA; these compounds can be identified at the Level 1 concentration but the standard deviation among replicates at this lower spike level resulted in a higher reporting limit.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.5 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 ASTM Standards:⁵

[D1193 Specification for Reagent Water](#)
[D2777 Practice for Determination of Precision and Bias of Applicable Test Methods of Committee D19 on Water](#)
[D5847 Practice for Writing Quality Control Specifications for Standard Test Methods for Water Analysis](#)
[E2554 Practice for Estimating and Monitoring the Uncertainty of Test Results of a Test Method Using Control Chart Techniques](#)

¹ This test method is under the jurisdiction of ASTM Committee D34 on Waste Management and is the direct responsibility of Subcommittee D34.01.06 on Analytical Methods.

Current edition approved Sept. 1, 2017. Published September 2017. Originally approved in 2014. Last previous edition approved in 2017 as D7968 – 17. DOI: 10.1520/D7968-17A.

² Washington, J. W., Naile, J. E., Jenkins, T. M., and Lynch, D. G., “Characterizing Fluorotelomer and Polyfluoroalkyl Substances in New and Aged Fluorotelomer-Based Polymers for Degradation Studies with GC/MS and LC/MS/MS,” *Environmental Science and Technology*, Vol 48, 2014, pp. 5762–5769.

³ The MDL is determined following the Code of Federal Regulations, 40 CFR Part 136, Appendix B utilizing solvent extraction of soil. Two-gram sample of Ottawa sand was utilized. A detailed process determining the MDL is explained in the reference and is beyond the scope of this standard to be explained here.

⁴ Reporting range concentration is calculated from [Table 2](#) concentrations assuming a 30- μ L injection of the Level 1 calibration standard for the PFCs, and the highest level calibration standard with a 10-mL final extract volume of a 2-g soil sample. Volume variations will change the reporting limit and ranges.

⁵ For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.