



Standard Test Method for Estimation of Net Heat of Combustion of Aviation Fuels¹

This standard is issued under the fixed designation D1405/D1405M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the Department of Defense.

1. Scope*

1.1 This test method covers the estimation of the net heat of combustion at constant pressure in SI units (megajoules per kilogram) or inch-pound units [Btu per pound].

1.2 This test method is purely empirical and is applicable only to liquid hydrocarbon fuels derived by normal refining processes from conventional crude oil, which conform to the requirements of specifications for aviation gasolines, or aircraft turbine and jet engine fuels of limited boiling ranges and compositions as described in [Note 1](#).

NOTE 1—The estimation of the net heat of combustion of a hydrocarbon fuel from aniline-gravity product is justifiable only when the fuel belongs to a well-defined class for which a relation between heat of combustion and aniline-gravity product has been derived from accurate experimental measurements on representative samples of that class. Even in this case, the possibility that the estimates may be in error by large amounts for individual fuels should be recognized. The classes of fuels used to establish the correlation presented in this test method are represented by the following specifications:

Fuel	Specification
Aviation gasoline fuels: Grades 80, 82, 100/130, and 115/145	Specification D910 Specification D6227 DEF STAN 91-90 NATO Code F-18
Aviation turbine fuels: JP-4, Avtag/FSII	MIL-DTL-5624 DEF STAN 91-88 NATO Code F-40
JP-5, Avcat/FSII	MIL-DTL-5624 DEF STAN 91-86 NATO Code F-44
Jet A, Jet A-1, Avtur	Specification D1655 DEF STAN 91-91 NATO Code F-35

1.3 This test method is not applicable to pure hydrocarbons. It is not intended as a substitute for experimental measurements of heat of combustion.

1.4 The heat of combustion may also be determined in SI units by Test Method [D4529](#). Test Method [D4529](#) requires calculation of a single equation for all aviation fuels with a precision equivalent to that of this test method.

1.5 The values stated in either SI units or inch-pound units are to be regarded separately as standard. The values stated in each system may not be exact equivalents; therefore, each system shall be used independently of the other. Combining values from the two systems may result in non-conformance with the standard.

1.6 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 ASTM Standards:²

- [D129](#) Test Method for Sulfur in Petroleum Products (General Bomb Method)
- [D240](#) Test Method for Heat of Combustion of Liquid Hydrocarbon Fuels by Bomb Calorimeter
- [D287](#) Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method)
- [D611](#) Test Methods for Aniline Point and Mixed Aniline Point of Petroleum Products and Hydrocarbon Solvents
- [D910](#) Specification for Aviation Gasolines
- [D941](#) Test Method for Density and Relative Density (Specific Gravity) of Liquids by Lipkin Bicapillary Pycnometer³
- [D1217](#) Test Method for Density and Relative Density (Specific Gravity) of Liquids by Bingham Pycnometer
- [D1250](#) Guide for Use of the Petroleum Measurement Tables
- [D1266](#) Test Method for Sulfur in Petroleum Products (Lamp Method)
- [D1298](#) Test Method for Density, Relative Density (Specific Gravity), or API Gravity of Crude Petroleum and Liquid

¹ This test method is under the jurisdiction of ASTM Committee [D02](#) on Petroleum Products and Lubricants and is the direct responsibility of Subcommittee [D02.05](#) on Properties of Fuels, Petroleum Coke and Carbon Material.

Current edition approved Dec. 1, 2008. Published January 2009. Originally approved in 1956. Last previous edition approved in 2006 as D1405-01(2006).

This test method has been approved by the sponsoring committee and accepted by the Cooperating Societies in accordance with established procedures. DOI: 10.1520/D1405_D1405M-08.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ Withdrawn. The last approved version of this historical standard is referenced on www.astm.org.

*A Summary of Changes section appears at the end of this standard.