



Designation: D 3963/D 3963M – 00a1

Standard Specification for Fabrication and Jobsite Handling of Epoxy-Coated Steel Reinforcing Bars¹

This standard is issued under the fixed designation D 3963/D 3963M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification covers the fabrication and jobsite requirements for deformed and plain steel reinforcing bars with protective epoxy coating applied in accordance with Specification A 775/A 775M.

1.2 This specification is applicable for orders in either SI units (as Specification D 3963M) or inch-pound units (as Specification D 3963).

1.3 The values stated in either SI units or inch-pound units are to be regarded separately as standard. Within the text, the inch-pound units are shown in brackets. The values stated in each system are not exact equivalents; therefore, each system must be used independently of the other. Combining values from the two systems may result in nonconformance with the specification.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 ASTM Standards:

A 775/A 775M Specification for Epoxy-Coated Reinforcing Steel Bars²

¹ This specification is under the jurisdiction of ASTM Committee D04 on Road and Paving Materials and is the direct responsibility of Subcommittee D04.36 on Bridge Deck Protective Systems.

Current edition approved July 10, 2000¹. Published September 2000. ~~March 2001~~. Originally published as D 3963 – 81. Last previous edition D 3963/D 3963M – 00a.