



Standard Test Method for Compressive Properties of Unidirectional Polymer Matrix Composite Materials Using a Sandwich Beam¹

This standard is issued under the fixed designation D 5467/D 5467M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method covers the in-plane compressive properties of polymer matrix composite materials reinforced by high-modulus fibers in a sandwich beam configuration. The composite material forms are limited to continuous-fiber composites of unidirectional orientation. This test procedure introduces compressive load into a thin skin bonded to a thick honeycomb core with the compressive load transmitted into the sample by subjecting the beam to four-point bending.

1.2 This procedure is applicable primarily to laminates made from prepreg or similar product forms. Other product forms may require deviations from the test method.

1.3 The values stated in either SI units or inch-pound units are to be regarded separately as standard. Within the text the inch-pounds units are shown in brackets. The values stated in each system are not exact equivalents; therefore, each system must be used independently of the other. Combining values from the two systems may result in nonconformance with the standard.

NOTE 1—Additional procedures for determining compressive properties of polymer matrix composites may be found in Test Methods D 3410/D 3410M and D 695.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 ASTM Standards:²

D 695 Test Method for Compressive Properties of Rigid Plastics

D 792 Test Methods for Density and Specific Gravity (Relative Density) of Plastics by Displacement
D 883 Terminology Relating to Plastics
D 2584 Test Method for Ignition Loss of Cured Reinforced Resins
D 2734 Test Method for Void Content of Reinforced Plastics
D 3171 Test Method for Constituent Content of Composite Materials
D 3410/D 3410M Test Method for Compressive Properties of Polymer Matrix Composite Materials with Unsupported Gage Section by Shear Loading
D 3878 Terminology for Composite Materials
D 5229/D 5229M Test Method for Moisture Absorption Properties and Equilibrium Conditioning of Polymer Matrix Composite Materials
E 4 Practices for Force Verification of Testing Machines
E 6 Terminology Relating to Methods of Mechanical Testing
E 111 Test Method for Young's Modulus, Tangent Modulus, and Chord Modulus
E 122 Practice for Calculating Sample Size to Estimate, With a Specified Tolerable Error, the Average for a Characteristic of a Lot or Process
E 177 Practice for Use of the Terms Precision and Bias in ASTM Test Methods
E 251 Test Methods for Performance Characteristics of Metallic Bonded Resistance Strain Gages
E 456 Terminology Relating to Quality and Statistics
E 1237 Guide for Installing Bonded Resistance Strain Gages
E 1309 Guide for Identification of Fiber-Reinforced Polymer-Matrix Composite Materials in Databases
E 1434 Guide for Recording Mechanical Test Data of Fiber-Reinforced Composite Materials in Databases
E 1471 Guide for Identification of Fibers, Fillers, and Core Materials in Computerized Material Property Databases

3. Terminology

3.1 *Definitions*—Terminology D 3878 defines terms relating to high-modulus fibers and their composites. Terminology D 883 defines terms relating to plastics. Terminology E 6 defines terms relating to mechanical testing. Terminology

¹ This test method is under the jurisdiction of ASTM Committee D30 on Composite Materials and is the direct responsibility of Subcommittee D30.04 on Lamina and Laminate Test Methods.

Current edition approved Mar. 1, 2004. Published March 2004. Originally approved in 1993. Last previous edition approved in 1997 as D 5467/D 5467M – 97^{ε1}.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

